

Edgeless Ground

Static White



Date: _____ Quantity: _____

Company: _____

Project: _____

Edgeless Ground is a sleek lighting solution designed for seamless integration. Its trimless design offers a clean, unobtrusive look, while advanced anti-glare technology ensures comfortable, glare-free illumination. Perfect for both residential and commercial spaces, this fixture combines aesthetics with performance.

FEATURES

- Trimless design for seamless integration
- Anti-glare grid enhances visual comfort
- High density 6063 aluminium profile
- Versatile beam angles

PERFORMANCE AND COMPLIANCE




ThermoSafe™

QUICK SPEC


Color Options	2700K, 3000K, 3500K, 4000K, 5000K, 6500K
Length	500mm [19.69"], 1000mm [39.37"]
Optics	
Standard (Clear Lens):	15°, 25°, 40°, 20°x55°
With anti-glare grid:	15°, 25°, 30°x40°, 20°x55°
Power Consumption	18W (500mm), 36W (1000mm)
Voltage	100-277VAC 50/60Hz
Dimming	ON/OFF, 0-10V, DALI, TRIAC, ELV
	* TRIAC and ELV dimming only available in US region
Max Static Load	Max 150kg
Impact speed	Max 15Km/hr

DIMENSIONS

Top View



Side View



Specifications are subject to change due to updates and innovations. Check our website for the latest technical data. The information serves as an estimate and may differ by power supply and installation. All rights reserved.

Sales@luminoscape.com

1 / 6

©2025 Luminoscape Lighting EDG2501

Edgeless Ground
Static White

PHYSICAL

Housing Material	Precise machine high density aluminium
Gasket	Silcone Rubber
Rubber Ring	Corrosion resistance silicon
Lens Material	Optical grade PMMA

CABLE CORE COLOR CODING


Cable	Function	Core(US)	Wire Size	Core(EU)	Wire Size
Power lead in (ON/OFF, TRIAC)	L (live)	Black	16AWG	Brown	1.3mm ²
	N (Neutral)	White	16AWG	Blue	1.3mm ²
	GND (Earth)	Green	16AWG	'ellow/Green	1.3mm ²
Power and Data Combined Lead-in/ Extension	L (live)	Black	16AWG	Brown	1.3mm ²
	N (Neutral)	White	16AWG	Blue	1.3mm ²
	GND (Earth)	Green	16AWG	'ellow/Green	1.3mm ²
	DIM+	Purple	22AWG	Purple	0.3mm ²
	DIM-	Pink	22AWG	Grey	0.3mm ²
	N/A	Yellow	22AWG	Yellow	0.3mm ²

SET BACK DISTANCE

Correct setback distances ensure optimal lighting performance and effective wallwashing results

Recommended Setback Distances for Wallwashers

Set Back Distance	Purpose	Best Use
20mm-50mm	smooth surfaces,	Focused, intense lighting.
50mm-100mm	Balanced lighting for textured walls.	General wallwashing
100mm-200mm	Wide, even light for large areas.	Enhances textured surfaces







Noted:

- Our recommended setback distances are only guidelines. The actual distance may vary depending on the specific wall texture, height, and lighting effect required for your project. Always adjust based on real-world conditions to achieve the best outcome.

Edgeless Ground

Static White


CONNECTING ACCESSORIES (Order Separately)

ITEM: Paguro 5650/3**Brand:** STEAB**Dimming:** ON OFF, TRIAC**Description:** GEL Box 2ways waterproof IP68 3 pin connectorsFor more details, please visit <https://www.steab.it/catalogo/paguro-5695-3/?lang=en>**ITEM:** Paguro 5760/13**Brand:** STEAB**Diming type:** 0-10V, DALI**Description:** 2-Way Gel-Filled IP68 Waterproof 6-Pin ConnectorFor more details, please visit <https://www.steab.it/catalogo/quick-paguro-5760-13-3/?lang=en>

Edgeless Ground

Static White

INSTALLATION PREPARATION



Cut-out Dimension: 42mm x 502mm /1002mm

Remarks:

- Ensure adequate drainage during installation; failure to do so will void the warranty.
- Ensure that the wire is connected with sealed or gel-filled connectors
- Use stainless steel screws for mounting the trim.
- Ensure the top side is level with the ground surface

Edgeless Ground
Static White

PARTCODE BUILDER

EXAMPLE CODE: EDG.05.30.40.CL-ONOF-MS-PB-EU

Series	Length	Color Option	Optic	Diffused Option	Control	Mounting Option	Finish	Area
EDG Edgeless Ground Static White	05 500mm	27 2700K	15 15°	CL Clear Lens	ONOF ON/OFF	NA N/A	PB Black	EU EUROPE
	10 1000mm	30 3000K	25 25°	AG Anti-glare Grid	010V 0-10V	MS Mounting Sleeve		US USA
		35 3500K	40 40°		DALI DALI			
		40 4000K	2055 20°x55°		TRI TRIAC			
		50 5000K			ELV ELV			
		65 6500K						

- Remarks:**
- Anti-glare grid changes field of view to 30°x40° (from 40°)
 - The standard loop in cable is 1 meter long with open terminals
 - Customized optic available
 - Customized marine-grade coating available
 - Customized RAL color coating available
 - TRIAC and ELV dimming only available in US region

Luminoscape regularly enhances its optics for ongoing product improvement. Luminoscape reserves the right to modify the optics without prior notice. For repeated or project orders requiring the same optic and control; kindly include the relevant Luminoscape invoice number (LS-INVxxxxx) in the purchase order.

Edgeless Ground

Static White

Statement of Limited Warranty

Disclaimer of Warranty:

Luminoscape products are tested and manufactured to meet the highest quality standards. We offer a limited warranty that covers defects in materials and workmanship for a period of 5 years from the date of purchase for standard products, and 3 years for inground and customized products. For customized products, please consult your sales representative for confirmation of warranty terms. The determination of whether a product is defective will be made by Luminoscape. Should any product be deemed defective in materials or workmanship, Luminoscape will, at its discretion, repair or replace the product at no charge. Luminoscape reserves the right to use similar, new, repaired, or remanufactured products or parts as part of this limited warranty process.

This warranty is expressly limited to the repair or replacement of the product. In no case shall the total remedy exceed the purchase price of the defective product. Luminoscape shall not be liable for any incidental or consequential damages arising from or related to the use of the products.

Warranty Period:

Luminoscape provides a standard warranty of 5 years for our products. For inground and customized orders, the warranty period is 3 years. In exceptional cases, further details regarding the warranty period may be discussed with your sales representative.

Warranty Protection:

This limited warranty does not apply where

- Products that have been improperly modified, adjusted, repaired or any alterations.
- Products that are damaged due to improper installation or connection not in accordance with the product wiring diagram.
- Products that have been improperly modified, adjusted, repaired or any alterations.
- Damage from any "Acts of God" includes floods, lightning, landslides, earthquakes, tornadoes, hurricanes and wildfires.
- Damage results from electrical power surges and spikes.
- Products used in an inappropriate environmental conditions (temperature, humidity, moisture, etc.) outside the normal specified range.
- Electrical power surges and spikes.
- Products are damaged due to chemical exposure or corrosion.
- Products have exceeded their operational lifespan as specified in the product documentation.
- Please consult your sales representative for any specific warranty questions or concerns.

Remark: No distributor or supplier of Luminoscape has the authority to modify or amend this Limited Warranty. This warranty may not be transferred or assigned by the original end user.