

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	1115.5 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	99.2V x 94.9H
	At 50% of Imax	48.5V x 47.8H
	At 90% of Imax	19.1V x 18.9H

Beam Flux	Total	999.7 lumens per klm.
	To 10% of Imax	852.0 lumens per klm.
	To 50% of Imax	436.9 lumens per klm.
	To 90% of Imax	90.6 lumens per klm.

Upward LOR	1.8 %
Downward LOR	98.2 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-08-14

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:DecoBody-330mm-RGBW BLUE-50D-Rev1	TYPE:RGBW-Blue	WEIGHT:
SPEC.:50 DEG	DIM.:330mm	SERIAL No.:IES001522
MFR.:	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:9.09lm/W	
MODEL		Imax(cd)	113.7
NOMINAL POWER(W)	11.3	AVAILABILITY(%)	85.2
RATED VOLTAGE(V)	220	Avai. FLUX(lm)	86.82
NOMINAL FLUX(lm)	101.9	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	101.9
TEST VOLTAGE(V)	221.4	q @50%(H,V)	48,48DEG

		AREA FLUX DIAGRAM														UNIT:lm				F t	F a
VERTICAL (DEG)	72	0.01	0.01	0.02	0.03	0.03	0.05	0.05	0.06	0.07	0.07	0.06	0.05	0.04	0.03	0.02	0.02	0.01	0.00	0.64	0.00
	64	0.01	0.02	0.03	0.04	0.06	0.08	0.09	0.11	0.12	0.12	0.11	0.09	0.07	0.06	0.04	0.02	0.01	0.01	1.08	0.00
	56	0.01	0.02	0.04	0.06	0.09	0.12	0.16	0.18	0.20	0.20	0.18	0.15	0.12	0.08	0.06	0.03	0.02	0.01	1.73	0.21
	48	0.01	0.03	0.05	0.08	0.13	0.19	0.25	0.31	0.34	0.34	0.30	0.24	0.18	0.12	0.08	0.05	0.02	0.01	2.72	1.85
	40	0.01	0.03	0.06	0.11	0.18	0.28	0.39	0.50	0.57	0.56	0.49	0.38	0.26	0.17	0.10	0.06	0.03	0.01	4.20	3.59
	32	0.02	0.04	0.08	0.14	0.25	0.40	0.59	0.78	0.90	0.90	0.76	0.57	0.38	0.23	0.13	0.07	0.03	0.01	6.28	5.80
	24	0.02	0.04	0.09	0.17	0.32	0.54	0.84	1.15	1.35	1.34	1.12	0.80	0.51	0.30	0.16	0.08	0.04	0.01	8.91	8.50
		0.02	0.05	0.10	0.20	0.38	0.68	1.09	1.53	1.81	1.81	1.50	1.05	0.65	0.36	0.19	0.09	0.04	0.02	11.6	11.2
		0.02	0.05	0.11	0.22	0.42	0.76	1.25	1.76	2.10	2.10	1.77	1.25	0.75	0.40	0.20	0.09	0.04	0.02	13.3	12.9
		0.02	0.05	0.10	0.21	0.42	0.76	1.25	1.77	2.11	2.11	1.79	1.26	0.75	0.40	0.20	0.09	0.04	0.02	13.4	13.0
		0.02	0.05	0.10	0.20	0.38	0.67	1.09	1.53	1.81	1.81	1.52	1.09	0.66	0.36	0.18	0.09	0.04	0.01	11.6	11.2
	-24	0.02	0.04	0.08	0.16	0.31	0.53	0.82	1.12	1.32	1.32	1.12	0.82	0.52	0.30	0.16	0.08	0.04	0.01	8.76	8.35
	-32	0.02	0.03	0.07	0.13	0.23	0.38	0.56	0.73	0.85	0.85	0.73	0.56	0.37	0.23	0.13	0.07	0.03	0.01	5.97	5.48
	-40	0.01	0.03	0.05	0.10	0.16	0.25	0.36	0.45	0.52	0.52	0.45	0.36	0.25	0.16	0.09	0.05	0.02	0.01	3.85	3.23
	-48	0.01	0.02	0.04	0.07	0.11	0.16	0.22	0.27	0.30	0.30	0.27	0.22	0.16	0.11	0.07	0.04	0.02	0.01	2.40	1.43
	-56	0.01	0.02	0.03	0.05	0.07	0.10	0.13	0.16	0.17	0.17	0.16	0.13	0.10	0.07	0.05	0.03	0.01	0.01	1.45	0.00
-64	0.01	0.01	0.02	0.03	0.04	0.06	0.07	0.09	0.10	0.10	0.09	0.08	0.06	0.04	0.03	0.02	0.01	0.00	0.85	0.00	
-72	0.00	0.01	0.01	0.02	0.02	0.03	0.04	0.05	0.05	0.05	0.05	0.04	0.03	0.02	0.02	0.01	0.01	0.00	0.46	0.00	
	-72	-64	-56	-48	-40	-32	-24	-16	HORIZONTAL (DEG)				16	24	32	40	48	56	64	72	
F t	0.24	0.53	1.06	2.00	3.59	6.04	9.26	12.6	14.7	14.7	12.5	9.14	5.88	3.45	1.89	0.98	0.46	0.19	99	---	
F a	0.00	0.00	0.00	1.06	2.83	5.34	8.61	11.9	14.1	14.0	11.8	8.47	5.17	2.65	0.85	0.00	0.00	0.00	---	87	

one-half-peak spread: U:24.0,D:24.8 , L:24.5,R:23.6


NEMA Beam Type: Type 5

H_(b) Range: -90 - 90DEG
 H_(b) Interval: 0.5DEG
 Test Speed: LOW
 Temperature: 25.3DEG
 Operators: Fan
 Test Date: 2023-08-14

V(B) Range: -180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 8.630m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: DLF.03.TX50.14(30).LDBV50	TYPE:RGBW 3000K-Blue	WEIGHT:
SPEC.:50 DEG	DIM.: 330 mm	SERIAL No.:IES001522
MFR.:	SUR.:	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-08-14

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: DLF.03.TX50.14 (30) .LDBV50	TYPE:RGBW 3000K-Blue	WEIGHT:
SPEC.:50 DEG	DIM.: 330 mm	SERIAL No.:IES001522
MFR.:	SUR.:	Shielding Angle:



H_b Range: -90 - 90DEG
H_b Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-08-14

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(b) Range: -90 - 90DEG
H(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-08-14

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME: DLF.03.TX50.14(30).LDBV50	TYPE:RGBW 3000K-Blue	WEIGHT:
SPEC.:50 DEG	DIM.: 330 mm	SERIAL No.:IES001522
MFR.:	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-08-14

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: DLF.03.TX50.14(30).LDBV50	TYPE:RGBW 3000K-Blue	WEIGHT:
SPEC.:50 DEG	DIM.: 330 mm	SERIAL No.:IES001522
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.36	0.34	0.33	0.33	0.34	0.36	0.39	0.43	0.49	0.55	0.59	0.63	0.64	0.64	0.64	0.64	0.63	0.62	0.63
-170	0.36	0.33	0.32	0.31	0.30	0.31	0.33	0.36	0.39	0.42	0.44	0.46	0.46	0.46	0.46	0.47	0.49	0.50	0.55
-160	0.36	0.32	0.30	0.28	0.27	0.27	0.27	0.27	0.28	0.28	0.29	0.28	0.27	0.31	0.35	0.37	0.39	0.43	0.46
-150	0.36	0.31	0.29	0.26	0.24	0.22	0.21	0.19	0.18	0.16	0.15	0.18	0.20	0.23	0.25	0.27	0.30	0.33	0.35
-140	0.36	0.31	0.27	0.24	0.21	0.18	0.16	0.13	0.10	0.10	0.11	0.12	0.14	0.14	0.15	0.18	0.21	0.23	0.24
-130	0.36	0.30	0.26	0.22	0.19	0.15	0.12	0.08	0.07	0.07	0.07	0.07	0.07	0.08	0.09	0.11	0.12	0.14	0.14
-120	0.36	0.30	0.25	0.21	0.17	0.12	0.09	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.06	0.08	0.09	0.09
-110	0.36	0.29	0.24	0.20	0.15	0.11	0.06	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.05	0.05	0.06	0.06
-100	0.36	0.30	0.24	0.19	0.14	0.09	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.05	0.05
-90	0.36	0.31	0.25	0.20	0.14	0.09	0.03	0.03	0.03	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.03	0.03	0.03
-80	0.36	0.31	0.26	0.21	0.16	0.12	0.08	0.14	0.20	0.25	0.31	0.36	0.42	0.46	0.50	0.53	0.56	0.59	0.61
-70	0.36	0.32	0.29	0.28	0.33	0.39	0.48	0.62	0.80	0.97	1.13	1.30	1.47	1.64	1.80	1.93	2.05	2.14	2.19
-60	0.36	0.33	0.34	0.46	0.62	0.83	1.05	1.28	1.61	1.98	2.39	2.82	3.25	3.67	4.05	4.38	4.65	4.84	4.95
-50	0.36	0.35	0.45	0.67	0.98	1.33	1.70	2.12	2.71	3.44	4.25	5.16	6.13	7.12	8.05	8.86	9.51	9.96	10.2
-40	0.36	0.37	0.55	0.89	1.35	1.86	2.45	3.22	4.14	5.41	6.99	8.80	10.8	13.0	15.2	17.2	18.9	20.0	20.5
-30	0.36	0.39	0.66	1.12	1.72	2.39	3.27	4.43	5.99	7.98	10.6	14.0	18.0	22.5	27.1	31.5	35.5	38.3	39.4
-20	0.36	0.42	0.77	1.32	2.02	2.87	4.03	5.64	7.85	10.9	15.0	20.4	27.3	35.5	44.6	53.7	61.8	67.7	69.9
-10	0.36	0.44	0.83	1.45	2.25	3.24	4.62	6.57	9.30	13.2	18.7	26.1	35.8	48.3	62.8	77.7	90.1	98.4	102
0	0.36	0.45	0.87	1.53	2.38	3.44	4.92	7.00	9.97	14.3	20.2	28.3	39.2	53.2	69.4	85.8	100	110	114
10	0.36	0.45	0.86	1.51	2.34	3.36	4.78	6.77	9.58	13.6	19.0	26.5	36.2	48.4	62.4	76.8	89.6	98.4	101
20	0.36	0.44	0.82	1.41	2.18	3.09	4.33	6.02	8.35	11.5	15.7	21.2	28.2	36.6	46.0	55.5	63.9	69.3	71.2
30	0.36	0.43	0.74	1.25	1.94	2.70	3.68	4.97	6.63	8.84	11.6	15.2	19.4	24.2	29.3	34.2	38.3	41.1	42.3
40	0.36	0.42	0.65	1.05	1.62	2.24	2.94	3.83	4.93	6.30	8.04	10.0	12.3	14.7	17.2	19.3	21.1	22.4	22.9
50	0.36	0.41	0.56	0.85	1.25	1.73	2.23	2.79	3.46	4.28	5.22	6.26	7.38	8.53	9.54	10.4	11.2	11.7	11.9
60	0.36	0.40	0.48	0.65	0.89	1.20	1.56	1.91	2.29	2.71	3.18	3.69	4.21	4.71	5.14	5.53	5.83	6.04	6.15
70	0.36	0.39	0.43	0.50	0.61	0.76	0.92	1.11	1.33	1.54	1.74	1.95	2.15	2.36	2.55	2.71	2.85	2.95	3.02
80	0.36	0.38	0.40	0.43	0.46	0.50	0.54	0.58	0.64	0.70	0.77	0.84	0.90	0.96	1.02	1.07	1.11	1.14	1.17
90	0.36	0.37	0.38	0.39	0.41	0.42	0.43	0.42	0.42	0.41	0.40	0.40	0.39	0.40	0.40	0.41	0.41	0.42	0.42
100	0.36	0.36	0.37	0.38	0.38	0.38	0.39	0.38	0.36	0.36	0.35	0.35	0.34	0.34	0.35	0.35	0.35	0.35	0.36
110	0.36	0.35	0.36	0.36	0.36	0.36	0.36	0.35	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34
120	0.36	0.35	0.35	0.35	0.35	0.34	0.34	0.34	0.33	0.34	0.34	0.35	0.36	0.37	0.37	0.37	0.36	0.35	0.34
130	0.36	0.35	0.34	0.34	0.34	0.34	0.33	0.33	0.34	0.35	0.36	0.38	0.41	0.44	0.45	0.45	0.45	0.45	0.44
140	0.36	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.35	0.37	0.42	0.45	0.49	0.52	0.55	0.55	0.56	0.56	0.55
150	0.36	0.34	0.34	0.34	0.33	0.34	0.35	0.36	0.39	0.42	0.46	0.50	0.55	0.59	0.62	0.64	0.64	0.63	0.62
160	0.36	0.34	0.34	0.34	0.34	0.35	0.37	0.39	0.43	0.47	0.52	0.56	0.58	0.62	0.63	0.64	0.64	0.65	0.65
170	0.36	0.34	0.34	0.33	0.34	0.35	0.38	0.42	0.47	0.52	0.57	0.60	0.62	0.63	0.64	0.64	0.64	0.63	0.65
180	0.36	0.34	0.33	0.33	0.34	0.36	0.39	0.43	0.49	0.55	0.59	0.63	0.64	0.64	0.64	0.64	0.63	0.62	0.65

H_(b) Range: -90 - 90DEG
 H_(b) Interval: 0.5DEG
 Test Speed: LOW
 Temperature: 25.3DEG
 Operators: Fan
 Test Date: 2023-08-14

V(B) Range: -180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 8.630m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: DLF.03.TX50.14(30).LDBV50	TYPE:RGBW 3000K-Blue	WEIGHT:
SPEC.:50 DEG	DIM.: 330 mm	SERIAL No.:IES001522
MFR.:	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H(DEC) V(DEC)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
-180	0.54	0.49	0.45	0.41	0.35	0.29	0.23	0.18	0.13	0.09	0.06	0.05	0.04	0.02	0.02	0.02	0.02	0.03
-170	0.49	0.47	0.46	0.41	0.36	0.30	0.24	0.19	0.14	0.10	0.07	0.05	0.04	0.03	0.03	0.02	0.02	0.03
-160	0.44	0.38	0.36	0.34	0.31	0.28	0.22	0.18	0.14	0.10	0.07	0.06	0.04	0.03	0.03	0.03	0.02	0.03
-150	0.33	0.30	0.27	0.25	0.23	0.21	0.18	0.15	0.13	0.09	0.08	0.06	0.04	0.04	0.03	0.03	0.02	0.03
-140	0.23	0.21	0.18	0.15	0.14	0.13	0.12	0.11	0.10	0.09	0.07	0.05	0.05	0.04	0.03	0.03	0.02	0.03
-130	0.14	0.12	0.11	0.09	0.08	0.07	0.07	0.08	0.07	0.07	0.07	0.05	0.04	0.04	0.03	0.03	0.03	0.03
-120	0.09	0.08	0.07	0.06	0.05	0.05	0.05	0.06	0.06	0.06	0.06	0.05	0.04	0.04	0.04	0.03	0.03	0.03
-110	0.06	0.06	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.03	0.03	0.03
-100	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.03	0.03	0.03	0.03
-90	0.03	0.04	0.04	0.04	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.03	0.03	0.03
-80	0.59	0.56	0.53	0.49	0.45	0.40	0.35	0.29	0.24	0.19	0.13	0.08	0.06	0.05	0.05	0.04	0.03	0.03
-70	2.14	2.07	1.96	1.83	1.68	1.51	1.32	1.12	0.94	0.77	0.61	0.45	0.31	0.21	0.11	0.06	0.04	0.03
-60	4.86	4.69	4.44	4.12	3.75	3.33	2.88	2.42	1.99	1.59	1.23	0.95	0.70	0.46	0.26	0.12	0.05	0.03
-50	9.97	9.55	8.91	8.13	7.20	6.20	5.23	4.31	3.47	2.71	2.06	1.54	1.11	0.76	0.43	0.20	0.06	0.03
-40	20.0	18.9	17.3	15.3	13.1	10.8	8.77	6.98	5.41	4.12	3.07	2.22	1.55	1.04	0.63	0.29	0.07	0.03
-30	38.4	35.7	31.7	27.1	22.4	17.8	13.8	10.4	7.81	5.74	4.15	2.93	2.00	1.31	0.80	0.35	0.09	0.03
-20	67.6	61.7	53.6	44.4	35.2	26.9	19.9	14.4	10.3	7.34	5.14	3.54	2.37	1.52	0.92	0.42	0.11	0.03
-10	98.1	89.9	77.4	62.7	48.0	35.2	25.2	17.7	12.3	8.51	5.83	3.96	2.63	1.66	1.00	0.47	0.13	0.03
0	111	102	87.9	70.8	53.5	38.7	27.2	18.8	13.0	8.88	6.04	4.07	2.69	1.71	1.03	0.48	0.13	0.03
10	97.9	88.7	75.4	60.7	46.7	34.6	24.9	17.7	12.4	8.66	5.96	4.07	2.72	1.73	1.05	0.49	0.14	0.03
20	68.5	62.4	53.5	43.8	34.5	26.2	19.7	14.5	10.6	7.63	5.40	3.77	2.55	1.65	1.01	0.47	0.14	0.03
30	40.6	37.3	32.9	27.9	22.9	18.2	14.2	10.9	8.28	6.17	4.53	3.24	2.25	1.49	0.93	0.43	0.13	0.03
40	22.1	20.6	18.7	16.5	14.0	11.7	9.55	7.64	6.04	4.68	3.55	2.62	1.86	1.27	0.78	0.38	0.12	0.03
50	11.6	11.0	10.2	9.28	8.25	7.14	6.05	5.04	4.12	3.31	2.61	1.97	1.46	1.02	0.60	0.31	0.12	0.03
60	6.01	5.77	5.46	5.06	4.62	4.12	3.59	3.08	2.60	2.16	1.77	1.40	1.05	0.71	0.45	0.25	0.11	0.03
70	2.95	2.83	2.69	2.52	2.32	2.10	1.88	1.66	1.46	1.27	1.08	0.87	0.66	0.48	0.32	0.20	0.11	0.03
80	1.13	1.09	1.04	0.98	0.92	0.85	0.79	0.73	0.67	0.61	0.56	0.52	0.43	0.34	0.26	0.18	0.10	0.03
90	0.42	0.42	0.41	0.41	0.40	0.40	0.41	0.41	0.42	0.43	0.43	0.44	0.37	0.30	0.23	0.16	0.10	0.03
100	0.35	0.35	0.35	0.35	0.34	0.34	0.34	0.35	0.35	0.36	0.37	0.38	0.32	0.27	0.21	0.15	0.09	0.03
110	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.34	0.35	0.34	0.34	0.29	0.24	0.19	0.14	0.08
120	0.35	0.36	0.37	0.37	0.37	0.35	0.35	0.34	0.34	0.34	0.33	0.31	0.26	0.22	0.17	0.13	0.08	0.03
130	0.45	0.45	0.45	0.45	0.44	0.41	0.39	0.36	0.35	0.34	0.31	0.27	0.23	0.19	0.15	0.11	0.07	0.03
140	0.56	0.56	0.56	0.55	0.52	0.48	0.45	0.43	0.37	0.33	0.28	0.23	0.20	0.16	0.13	0.10	0.06	0.03
150	0.63	0.63	0.64	0.62	0.59	0.55	0.50	0.46	0.38	0.30	0.24	0.20	0.16	0.13	0.10	0.08	0.05	0.03
160	0.64	0.64	0.64	0.63	0.62	0.58	0.51	0.41	0.33	0.26	0.20	0.15	0.12	0.10	0.08	0.06	0.04	0.03
170	0.64	0.64	0.64	0.60	0.53	0.46	0.38	0.31	0.24	0.19	0.13	0.10	0.08	0.06	0.05	0.04	0.03	0.03
180	0.54	0.49	0.45	0.41	0.35	0.29	0.23	0.18	0.13	0.09	0.06	0.05	0.04	0.02	0.02	0.02	0.02	0.03

H_(b) Range: -90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature:25.3DEG

Operators:Fan

Test Date:2023-08-14

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks: