

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity (Luminaire orientation as tested.)		2550.7 cd per klm. 0.0 degrees vertical 0.0 degrees horizontal
Beam Spread	At 10% of Imax	63.9V x 63.1H
	At 50% of Imax	27.8V x 27.6H
	At 90% of Imax	10.1V x 10.1H
Beam Flux	Total	1000.1 lumens per klm.
	To 10% of Imax	758.5 lumens per klm.
	To 50% of Imax	327.9 lumens per klm.
	To 90% of Imax	57.6 lumens per klm.
Upward LOR		2.2 %
Downward LOR		97.9 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-05-18

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: Medusa-510mm-RGBW GREEN-25D-Rev1	TYPE: RGBW-GREEN	WEIGHT:
SPEC.: 25 DEG	DIM.: 510mm	SERIAL No.: IES001033-G
MFR.:	SUR.:	Shielding Angle:



DATA OF LAMP		Eff: 30.93lm/W	
MODEL		Imax(cd)	591.8
NOMINAL POWER(W)	7.5	AVAILABILITY(%)	75.8
RATED VOLTAGE(V)	48	Avai. FLUX(lm)	176.0
NOMINAL FLUX(lm)	232	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	232.0
TEST VOLTAGE(V)	48	q @50%(H, V)	28, 28DEG

		AREA FLUX DIAGRAM																UNIT:lm				F t	F a
VERTICAL (DEG)	45	0.05	0.06	0.08	0.10	0.12	0.14	0.15	0.16	0.16	0.16	0.15	0.14	0.12	0.11	0.09	0.07	0.05	0.04	1.93	0.00		
	40	0.06	0.08	0.10	0.13	0.16	0.20	0.22	0.24	0.25	0.25	0.23	0.20	0.17	0.14	0.11	0.09	0.06	0.05	2.74	0.00		
	35	0.07	0.09	0.13	0.17	0.23	0.28	0.34	0.38	0.40	0.39	0.35	0.29	0.24	0.19	0.15	0.11	0.08	0.06	3.93	0.19		
	30	0.08	0.11	0.16	0.23	0.31	0.41	0.50	0.57	0.61	0.59	0.52	0.43	0.34	0.26	0.19	0.14	0.10	0.07	5.62	3.00		
	25	0.09	0.14	0.21	0.30	0.43	0.57	0.73	0.87	0.94	0.91	0.79	0.63	0.49	0.36	0.25	0.17	0.12	0.08	8.06	6.17		
	20	0.11	0.17	0.25	0.38	0.56	0.79	1.06	1.31	1.45	1.41	1.19	0.92	0.68	0.48	0.33	0.22	0.14	0.09	11.5	9.95		
	15	0.12	0.19	0.30	0.46	0.70	1.04	1.49	1.96	2.24	2.17	1.78	1.31	0.91	0.62	0.41	0.26	0.16	0.10	16.2	14.9		
		0.13	0.21	0.34	0.53	0.84	1.30	1.97	2.73	3.24	3.14	2.50	1.75	1.18	0.77	0.49	0.30	0.18	0.10	21.7	20.5		
		0.13	0.22	0.36	0.58	0.92	1.48	2.33	3.33	4.07	3.97	3.20	2.25	1.45	0.90	0.54	0.32	0.19	0.11	26.4	25.3		
		0.14	0.22	0.37	0.59	0.96	1.56	2.51	3.62	4.35	4.26	3.48	2.42	1.53	0.93	0.56	0.33	0.19	0.11	28.1	27.0		
		0.13	0.21	0.35	0.58	0.93	1.51	2.37	3.26	3.80	3.69	3.01	2.13	1.38	0.86	0.52	0.31	0.18	0.11	25.3	24.2		
	-15	0.12	0.20	0.32	0.52	0.82	1.26	1.83	2.43	2.79	2.72	2.25	1.65	1.12	0.72	0.46	0.28	0.16	0.10	19.7	18.5		
	-20	0.11	0.17	0.28	0.43	0.65	0.94	1.30	1.64	1.83	1.79	1.53	1.18	0.84	0.57	0.37	0.23	0.14	0.09	14.1	12.7		
	-25	0.09	0.14	0.22	0.34	0.49	0.67	0.88	1.06	1.16	1.14	1.00	0.80	0.60	0.43	0.29	0.19	0.12	0.08	9.71	8.10		
	-30	0.08	0.11	0.17	0.25	0.35	0.47	0.58	0.68	0.74	0.72	0.65	0.54	0.42	0.31	0.21	0.15	0.10	0.06	6.59	4.46		
	-35	0.06	0.09	0.13	0.18	0.24	0.31	0.38	0.44	0.47	0.46	0.42	0.35	0.28	0.21	0.16	0.11	0.08	0.05	4.42	1.03		
-40	0.05	0.07	0.10	0.13	0.17	0.21	0.25	0.28	0.29	0.29	0.26	0.23	0.19	0.15	0.11	0.08	0.06	0.04	2.95	0.00			
-45	0.04	0.05	0.07	0.09	0.12	0.14	0.16	0.17	0.18	0.18	0.17	0.15	0.13	0.10	0.08	0.06	0.05	0.04	1.98	0.00			
	-45	-40	-35	-30	-25	-20	-15	-10	HORIZONTAL (DEG)				10	15	20	25	30	35	40	45			
F t	1.65	2.55	3.93	6.00	8.99	13.3	19.1	25.1	29.0	28.2	23.5	17.4	12.1	8.11	5.33	3.41	2.15	1.36	211	---			
F a	0.00	0.00	0.56	3.69	7.15	11.6	17.5	23.7	27.6	26.8	22.0	15.8	10.3	6.14	2.87	0.16	0.00	0.00	---	176			

one-half-peak spread: U:14.0,D:14.1 , L:13.9,R:14.0


NEMA Beam Type: Type 4

H_(b) Range: -90 - 90DEG
 H_(b) Interval: 0.5DEG
 Test Speed: LOW
 Temperature: 25.3DEG
 Operators: Fan
 Test Date: 2023-05-18

V(B) Range: -180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 8.630m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: Medusa-510mm-RGBW GREEN-25D-Rev1	TYPE: RGBW-GREEN	WEIGHT:
SPEC.: 25 DEG	DIM.: 510mm	SERIAL No.: IES001033-G
MFR.:	SUR.:	Shielding Angle:




H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-05-18

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: Medusa-510mm-RGBW GREEN-25D-Rev1	TYPE: RGBW-GREEN	WEIGHT:
SPEC.: 25 DEG	DIM.: 510mm	SERIAL No.: IES001033-G
MFR.:	SUR.:	Shielding Angle:



H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-05-18

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H_b Range: -90 - 90DEG
H_b Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-05-18

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME: Medusa-510mm-RGBW GREEN-25D-Rev1	TYPE: RGBW-GREEN	WEIGHT:
SPEC.: 25 DEG	DIM.: 510mm	SERIAL No.: IES001033-G
MFR.:	SUR.:	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-05-18

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: Medusa-510mm-RGBW GREEN-25D-ReV1	TYPE: RGBW-GREEN	WEIGHT:
SPEC.: 25 DEG	DIM.: 510mm	SERIAL No.: IES001033-G
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.83	0.76	0.72	0.72	0.73	0.78	0.87	0.99	1.15	1.33	1.50	1.62	1.71	1.75	1.75	1.73	1.71	1.68	1.65
-170	0.83	0.75	0.70	0.68	0.68	0.70	0.75	0.82	0.91	1.01	1.09	1.15	1.20	1.21	1.21	1.23	1.33	1.40	1.52
-160	0.83	0.74	0.68	0.65	0.64	0.63	0.63	0.64	0.66	0.68	0.68	0.68	0.67	0.80	0.92	1.03	1.12	1.21	1.27
-150	0.83	0.73	0.66	0.63	0.60	0.57	0.54	0.50	0.46	0.41	0.36	0.42	0.49	0.58	0.65	0.73	0.82	0.88	0.93
-140	0.83	0.73	0.65	0.60	0.56	0.52	0.48	0.41	0.33	0.31	0.32	0.33	0.36	0.39	0.42	0.47	0.52	0.56	0.58
-130	0.83	0.72	0.64	0.58	0.53	0.48	0.43	0.38	0.34	0.32	0.32	0.33	0.33	0.34	0.34	0.34	0.35	0.35	0.35
-120	0.83	0.72	0.64	0.57	0.51	0.46	0.40	0.36	0.36	0.35	0.34	0.34	0.34	0.34	0.34	0.33	0.32	0.31	0.30
-110	0.83	0.73	0.64	0.57	0.49	0.44	0.38	0.36	0.36	0.35	0.35	0.35	0.34	0.34	0.34	0.33	0.31	0.30	0.28
-100	0.83	0.73	0.65	0.56	0.48	0.41	0.35	0.35	0.34	0.34	0.34	0.34	0.34	0.33	0.32	0.31	0.30	0.29	0.28
-90	0.83	0.75	0.66	0.57	0.49	0.40	0.32	0.33	0.34	0.35	0.36	0.37	0.38	0.36	0.34	0.32	0.30	0.27	0.25
-80	0.83	0.76	0.70	0.67	0.66	0.67	0.69	0.77	0.86	0.94	1.02	1.09	1.16	1.19	1.22	1.23	1.24	1.23	1.22
-70	0.83	0.78	0.79	0.83	0.92	1.04	1.23	1.43	1.63	1.83	2.02	2.22	2.40	2.55	2.66	2.75	2.82	2.86	2.86
-60	0.83	0.81	0.87	0.98	1.17	1.43	1.78	2.21	2.60	3.01	3.45	3.89	4.34	4.76	5.12	5.42	5.66	5.80	5.85
-50	0.83	0.85	0.95	1.12	1.39	1.78	2.45	3.15	3.86	4.68	5.60	6.63	7.78	8.96	10.1	11.1	11.9	12.4	12.5
-40	0.83	0.88	1.00	1.22	1.56	2.34	3.31	4.37	5.58	7.09	9.01	11.5	14.4	17.8	21.4	24.8	27.7	29.6	30.2
-30	0.83	0.89	1.05	1.29	1.82	2.94	4.29	5.94	7.96	10.5	14.3	19.7	27.0	36.2	46.8	58.2	68.0	75.0	77.1
-20	0.83	0.91	1.08	1.31	2.11	3.50	5.31	7.70	10.5	14.7	21.3	31.6	47.0	67.7	94.2	126	160	185	193
-10	0.83	0.93	1.09	1.29	2.29	3.87	6.14	8.98	12.6	18.2	27.4	42.3	65.3	101	156	237	335	417	445
0	0.83	0.94	1.08	1.23	2.37	3.99	6.61	9.65	13.6	19.6	29.5	45.3	69.6	107	166	260	394	524	585
10	0.83	0.94	1.12	1.35	2.39	4.02	6.34	9.23	12.8	18.3	26.9	40.3	60.5	89.8	133	195	273	344	361
20	0.83	0.94	1.15	1.44	2.32	3.80	5.70	8.17	11.0	15.0	21.0	29.8	42.3	59.1	80.4	105	131	148	154
30	0.83	0.94	1.15	1.47	2.11	3.35	4.85	6.63	8.78	11.3	14.8	19.5	25.7	33.4	42.2	51.2	58.6	63.4	64.3
40	0.83	0.93	1.11	1.44	1.90	2.83	3.97	5.22	6.58	8.15	10.0	12.3	14.9	17.9	21.0	23.4	25.3	26.3	26.2
50	0.83	0.91	1.07	1.36	1.76	2.30	3.14	4.04	4.87	5.72	6.67	7.71	8.83	9.93	10.8	11.5	11.9	12.0	11.8
60	0.83	0.88	1.00	1.21	1.53	1.94	2.46	3.02	3.45	3.90	4.38	4.86	5.34	5.76	6.04	6.24	6.33	6.33	6.24
70	0.83	0.87	0.94	1.05	1.23	1.49	1.82	2.07	2.28	2.48	2.67	2.87	3.10	3.30	3.43	3.52	3.57	3.58	3.56
80	0.83	0.85	0.88	0.92	0.99	1.07	1.17	1.25	1.33	1.41	1.49	1.55	1.58	1.63	1.68	1.72	1.75	1.77	1.78
90	0.83	0.84	0.85	0.86	0.86	0.87	0.88	0.87	0.86	0.85	0.85	0.84	0.83	0.83	0.84	0.84	0.84	0.85	0.85
100	0.83	0.82	0.82	0.81	0.81	0.80	0.80	0.78	0.76	0.75	0.73	0.72	0.71	0.72	0.72	0.73	0.73	0.73	0.74
110	0.83	0.81	0.79	0.78	0.76	0.75	0.75	0.74	0.73	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72
120	0.83	0.79	0.77	0.75	0.74	0.73	0.72	0.72	0.72	0.73	0.74	0.76	0.79	0.81	0.83	0.84	0.85	0.85	0.85
130	0.83	0.79	0.75	0.73	0.73	0.72	0.72	0.72	0.73	0.78	0.84	0.90	0.97	1.04	1.09	1.14	1.17	1.19	1.20
140	0.83	0.78	0.73	0.72	0.72	0.72	0.73	0.76	0.82	0.91	1.01	1.12	1.24	1.34	1.43	1.49	1.53	1.56	1.56
150	0.83	0.77	0.73	0.72	0.72	0.73	0.76	0.84	0.93	1.06	1.20	1.34	1.47	1.58	1.67	1.74	1.77	1.79	1.78
160	0.83	0.77	0.72	0.72	0.72	0.75	0.81	0.91	1.05	1.21	1.36	1.49	1.60	1.70	1.77	1.81	1.84	1.85	1.87
170	0.83	0.76	0.72	0.72	0.73	0.76	0.85	0.96	1.13	1.30	1.46	1.59	1.68	1.74	1.78	1.79	1.80	1.79	1.84
180	0.83	0.76	0.72	0.72	0.73	0.78	0.87	0.99	1.15	1.33	1.50	1.62	1.71	1.75	1.75	1.73	1.71	1.68	1.69

H_(b) Range: -90 - 90DEG
 H_(b) Interval: 0.5DEG
 Test Speed: LOW
 Temperature: 25.3DEG
 Operators: Fan
 Test Date: 2023-05-18

V(B) Range: -180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 8.630m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: Medusa-510mm-RGBW GREEN-25D-ReV1	TYPE: RGBW-GREEN	WEIGHT:
SPEC.: 25 DEG	DIM.: 510mm	SERIAL No.: IES001033-G
MFR.:	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H(°) \ V(°)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	1.52	1.42	1.31	1.19	1.04	0.88	0.72	0.56	0.43	0.34	0.27	0.26	0.26	0.26	0.25	0.23	0.21	0.16	
-170	1.43	1.39	1.31	1.18	1.03	0.87	0.71	0.56	0.44	0.34	0.28	0.26	0.26	0.26	0.25	0.24	0.21	0.16	
-160	1.23	1.17	1.09	1.00	0.88	0.76	0.62	0.50	0.40	0.32	0.29	0.27	0.27	0.27	0.25	0.24	0.21	0.16	
-150	0.90	0.85	0.79	0.72	0.65	0.56	0.49	0.41	0.35	0.31	0.28	0.28	0.27	0.27	0.26	0.25	0.21	0.16	
-140	0.57	0.55	0.51	0.46	0.42	0.38	0.35	0.33	0.31	0.30	0.29	0.28	0.28	0.27	0.26	0.24	0.21	0.16	
-130	0.35	0.34	0.32	0.30	0.28	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.28	0.27	0.26	0.23	0.21	0.16	
-120	0.28	0.28	0.28	0.28	0.28	0.28	0.28	0.28	0.29	0.29	0.29	0.29	0.28	0.27	0.25	0.23	0.21	0.16	
-110	0.28	0.28	0.28	0.28	0.28	0.28	0.28	0.28	0.28	0.29	0.29	0.28	0.28	0.28	0.25	0.24	0.22	0.20	0.16
-100	0.28	0.27	0.26	0.26	0.25	0.24	0.24	0.25	0.25	0.26	0.26	0.26	0.25	0.24	0.23	0.21	0.19	0.16	
-90	0.25	0.26	0.26	0.26	0.26	0.26	0.26	0.25	0.25	0.25	0.24	0.24	0.23	0.21	0.20	0.18	0.17	0.16	
-80	1.20	1.17	1.13	1.09	1.03	0.97	0.90	0.83	0.75	0.66	0.58	0.48	0.37	0.28	0.22	0.18	0.17	0.16	
-70	2.81	2.72	2.60	2.47	2.31	2.13	1.95	1.76	1.56	1.37	1.18	0.95	0.68	0.46	0.31	0.21	0.17	0.16	
-60	5.69	5.45	5.13	4.74	4.32	3.91	3.49	3.06	2.64	2.25	1.89	1.41	0.97	0.63	0.39	0.24	0.17	0.16	
-50	12.1	11.4	10.4	9.23	8.08	6.94	5.87	4.93	4.09	3.37	2.68	1.97	1.29	0.75	0.45	0.26	0.18	0.16	
-40	28.8	26.1	22.8	19.1	15.7	12.6	9.97	7.84	6.12	4.78	3.63	2.62	1.73	0.89	0.46	0.26	0.17	0.16	
-30	72.7	63.7	52.7	41.4	31.4	23.1	16.7	12.1	8.81	6.53	4.87	3.36	2.21	1.14	0.44	0.25	0.17	0.16	
-20	178	148	114	83.7	58.7	39.7	26.4	17.6	12.0	8.34	5.94	4.08	2.55	1.31	0.37	0.22	0.16	0.16	
-10	393	304	210	139	90.4	57.6	36.0	22.6	14.6	9.76	6.72	4.74	2.72	1.39	0.34	0.17	0.15	0.16	
0	530	398	265	168	104	64.9	39.8	24.5	15.5	10.2	6.99	4.92	2.80	1.39	0.25	0.12	0.14	0.16	
10	323	242	170	118	80.9	53.6	34.5	22.1	14.6	9.90	6.90	4.91	2.85	1.50	0.41	0.21	0.17	0.16	
20	139	114	90.2	68.7	50.5	35.9	25.0	17.2	12.1	8.71	6.34	4.41	2.80	1.52	0.51	0.29	0.20	0.16	
30	59.6	51.7	42.2	35.2	28.3	21.8	16.4	12.3	9.38	7.14	5.47	3.82	2.58	1.44	0.63	0.36	0.22	0.16	
40	25.4	23.5	21.2	18.8	15.8	13.1	10.6	8.54	6.99	5.65	4.33	3.18	2.22	1.25	0.70	0.39	0.24	0.16	
50	11.7	11.3	10.6	9.76	8.69	7.72	6.74	5.83	4.97	4.22	3.49	2.67	1.83	1.14	0.70	0.41	0.26	0.16	
60	6.19	6.04	5.82	5.54	5.24	4.80	4.35	3.87	3.47	3.09	2.72	2.10	1.50	1.02	0.66	0.41	0.26	0.16	
70	3.51	3.43	3.32	3.18	3.00	2.82	2.66	2.49	2.30	2.09	1.88	1.59	1.18	0.84	0.59	0.41	0.27	0.16	
80	1.76	1.73	1.69	1.64	1.58	1.52	1.46	1.38	1.31	1.24	1.16	1.08	0.87	0.70	0.54	0.41	0.28	0.16	
90	0.85	0.85	0.85	0.85	0.85	0.85	0.86	0.86	0.87	0.88	0.88	0.89	0.77	0.64	0.52	0.40	0.28	0.16	
100	0.74	0.75	0.76	0.76	0.77	0.77	0.78	0.78	0.79	0.80	0.81	0.82	0.72	0.63	0.53	0.42	0.29	0.16	
110	0.73	0.75	0.76	0.77	0.78	0.78	0.78	0.77	0.77	0.78	0.78	0.76	0.68	0.59	0.50	0.40	0.30	0.16	
120	0.87	0.88	0.89	0.89	0.89	0.87	0.84	0.81	0.79	0.78	0.78	0.71	0.64	0.56	0.48	0.39	0.30	0.16	
130	1.21	1.21	1.20	1.18	1.14	1.08	1.01	0.94	0.88	0.84	0.75	0.67	0.59	0.52	0.45	0.37	0.28	0.16	
140	1.58	1.58	1.56	1.53	1.45	1.35	1.25	1.14	1.03	0.90	0.74	0.62	0.55	0.48	0.42	0.35	0.27	0.16	
150	1.81	1.82	1.80	1.75	1.67	1.57	1.45	1.33	1.11	0.87	0.70	0.57	0.49	0.44	0.38	0.33	0.26	0.16	
160	1.87	1.88	1.86	1.83	1.77	1.68	1.45	1.21	0.97	0.77	0.60	0.50	0.42	0.38	0.34	0.30	0.24	0.16	
170	1.79	1.81	1.81	1.70	1.54	1.35	1.14	0.93	0.74	0.58	0.46	0.39	0.35	0.32	0.29	0.27	0.23	0.16	
180	1.52	1.42	1.31	1.19	1.04	0.88	0.72	0.56	0.43	0.34	0.27	0.26	0.26	0.26	0.25	0.23	0.21	0.16	

H_(b) Range: -90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature: 25.3DEG

Operators: Fan

Test Date: 2023-05-18

V(B) Range: -180 - 180DEG

V(B) Interval: 0.5DEG

Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity: 65.0%

Test Distance: 8.630m [K=1.0000]

Remarks: