

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	5039.0 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	39.4V x 39.4H
	At 50% of Imax	20.7V x 20.3H
	At 90% of Imax	8.4V x 8.3H

Beam Flux	Total	1000.8 lumens per klm.
	To 10% of Imax	792.9 lumens per klm.
	To 50% of Imax	484.0 lumens per klm.
	To 90% of Imax	192.8 lumens per klm.

Upward LOR	1.5 %
Downward LOR	98.6 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:Astra D65-65mm-RGBW GREEN-20D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:20 DEG	DIA.:65MM	SERIAL No.:IES003424
MFR.:	SUR.:1	Shielding Angle:



DATA OF LAMP		Eff:49.05lm/W	
MODEL		Imax(cd)	593.1
NOMINAL POWER(W)	2.4	AVAILABILITY(%)	79.5
RATED VOLTAGE(V)	24	Avai. FLUX(lm)	93.56
NOMINAL FLUX(lm)	117.7	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	117.7
TEST VOLTAGE(V)	24	q @50%(H,V)	20,21DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm				F t	F a
	27	0.01	0.02	0.02	0.02	0.03	0.03	0.04	0.04	0.05	0.05	0.06	0.07	0.06	0.06	0.05	0.04	0.03	0.03	0.72	0.00	
	24	0.02	0.02	0.02	0.03	0.04	0.05	0.06	0.07	0.07	0.08	0.10	0.10	0.10	0.09	0.08	0.06	0.05	0.03	1.06	0.00	
	21	0.02	0.02	0.03	0.04	0.05	0.07	0.08	0.10	0.11	0.13	0.16	0.17	0.16	0.14	0.11	0.09	0.06	0.05	1.60	0.36	
	18	0.02	0.03	0.04	0.05	0.07	0.09	0.12	0.15	0.17	0.22	0.27	0.28	0.26	0.22	0.17	0.13	0.09	0.06	2.44	1.56	
	15	0.02	0.03	0.04	0.06	0.09	0.13	0.18	0.24	0.29	0.36	0.44	0.46	0.42	0.34	0.26	0.18	0.12	0.08	3.73	3.11	
	12	0.02	0.03	0.05	0.07	0.11	0.18	0.27	0.37	0.47	0.58	0.68	0.69	0.63	0.51	0.37	0.25	0.16	0.10	5.56	5.07	
	9	0.03	0.04	0.06	0.09	0.14	0.23	0.37	0.55	0.73	0.88	0.97	0.97	0.88	0.71	0.51	0.34	0.21	0.13	7.81	7.41	
		0.03	0.04	0.06	0.09	0.15	0.26	0.45	0.72	1.01	1.20	1.27	1.25	1.13	0.91	0.64	0.42	0.25	0.15	10.0	9.66	
		0.03	0.04	0.06	0.09	0.15	0.26	0.45	0.76	1.16	1.41	1.49	1.49	1.35	1.08	0.76	0.48	0.29	0.17	11.5	11.2	
		0.03	0.04	0.06	0.11	0.19	0.32	0.53	0.85	1.28	1.52	1.59	1.57	1.40	1.11	0.78	0.49	0.29	0.17	12.3	12.0	
		0.03	0.05	0.08	0.13	0.24	0.41	0.67	1.00	1.39	1.58	1.56	1.47	1.27	0.99	0.69	0.43	0.26	0.16	12.4	12.1	
	-9	0.03	0.05	0.08	0.14	0.25	0.43	0.67	0.97	1.28	1.43	1.40	1.28	1.07	0.81	0.56	0.36	0.22	0.13	11.2	10.8	
	-12	0.03	0.05	0.08	0.13	0.22	0.37	0.57	0.81	1.03	1.14	1.11	1.00	0.82	0.61	0.43	0.28	0.18	0.11	8.96	8.57	
	-15	0.03	0.04	0.07	0.11	0.17	0.27	0.41	0.58	0.72	0.79	0.78	0.69	0.57	0.43	0.31	0.21	0.14	0.09	6.39	5.91	
	-18	0.02	0.04	0.05	0.08	0.13	0.19	0.27	0.36	0.44	0.48	0.48	0.44	0.36	0.28	0.21	0.15	0.10	0.07	4.16	3.58	
-21	0.02	0.03	0.04	0.06	0.09	0.13	0.17	0.22	0.26	0.28	0.28	0.26	0.23	0.18	0.14	0.10	0.07	0.05	2.61	1.84		
-24	0.02	0.02	0.03	0.05	0.06	0.08	0.11	0.13	0.15	0.16	0.17	0.16	0.14	0.11	0.09	0.07	0.05	0.04	1.64	0.38		
-27	0.01	0.02	0.02	0.03	0.04	0.06	0.07	0.08	0.09	0.10	0.10	0.09	0.08	0.07	0.06	0.05	0.04	0.03	1.04	0.00		
	-27	-24	-21	-18	-15	-12	-9	-6	HORIZONTAL (DEG)				6	9	12	15	18	21	24	27		
F t	0.42	0.60	0.89	1.39	2.22	3.55	5.49	7.99	10.7	12.4	12.9	12.4	10.9	8.67	6.21	4.12	2.62	1.64	105	---		
F a	0.00	0.00	0.00	0.11	1.16	2.87	4.90	7.48	10.3	12.0	12.5	12.0	10.5	8.20	5.69	3.50	1.86	0.52	---	94		

one-half-peak spread: U:10.3,D:10.5 , L:9.6,R:10.8


NEMA Beam Type: Type 3

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:Astra D65-65mm-RGBW GREEN-20D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:20 DEG	DIA.:65MM	SERIAL No.:IES003424
MFR.:	SUR.:1	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:Astra D65-65mm-RGBW GREEN-20D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:20 DEG	DIA.:65MM	SERIAL No.:IES003424
MFR.:	SUR.:1	Shielding Angle:



H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME:Astra D65-65mm-RGBW GREEN-20D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:20 DEG	DIA.:65MM	SERIAL No.:IES003424
MFR.:	SUR.:1	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW GREEN-20D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:20 DEG	DIA.:65MM	SERIAL No.:IES003424
MFR.:	SUR.:1	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.22	0.20	0.19	0.19	0.20	0.26	0.36	0.51	0.67	0.79	0.81	0.80	0.79	0.78	0.75	0.68	0.57	0.57	0.58
-170	0.22	0.20	0.19	0.19	0.20	0.24	0.33	0.45	0.59	0.69	0.72	0.71	0.71	0.71	0.72	0.70	0.66	0.64	0.65
-160	0.22	0.20	0.19	0.18	0.19	0.22	0.27	0.37	0.48	0.57	0.62	0.62	0.61	0.61	0.61	0.62	0.63	0.62	0.61
-150	0.22	0.20	0.18	0.18	0.18	0.19	0.23	0.28	0.35	0.43	0.48	0.50	0.50	0.48	0.46	0.45	0.44	0.41	0.37
-140	0.22	0.19	0.18	0.18	0.17	0.17	0.19	0.21	0.24	0.28	0.32	0.34	0.35	0.34	0.31	0.28	0.24	0.20	0.14
-130	0.22	0.19	0.18	0.18	0.17	0.16	0.16	0.17	0.18	0.18	0.19	0.20	0.20	0.19	0.17	0.14	0.11	0.06	0.02
-120	0.22	0.19	0.19	0.17	0.17	0.16	0.16	0.16	0.15	0.14	0.14	0.14	0.12	0.10	0.09	0.07	0.05	0.04	0.01
-110	0.22	0.20	0.19	0.18	0.17	0.16	0.16	0.15	0.14	0.14	0.13	0.12	0.12	0.11	0.10	0.09	0.08	0.08	0.07
-100	0.22	0.21	0.19	0.18	0.17	0.17	0.16	0.15	0.14	0.14	0.13	0.12	0.12	0.11	0.11	0.10	0.09	0.09	0.08
-90	0.22	0.21	0.20	0.19	0.19	0.18	0.17	0.16	0.16	0.15	0.14	0.13	0.13	0.12	0.11	0.10	0.10	0.09	0.08
-80	0.22	0.22	0.22	0.21	0.21	0.21	0.20	0.19	0.19	0.18	0.17	0.16	0.16	0.15	0.14	0.14	0.13	0.12	0.11
-70	0.22	0.22	0.23	0.23	0.24	0.24	0.25	0.26	0.28	0.30	0.31	0.32	0.34	0.34	0.35	0.35	0.35	0.35	0.34
-60	0.22	0.23	0.24	0.26	0.28	0.30	0.35	0.39	0.44	0.48	0.53	0.57	0.61	0.65	0.68	0.70	0.71	0.71	0.69
-50	0.22	0.24	0.26	0.28	0.33	0.39	0.47	0.55	0.63	0.74	0.84	0.95	1.06	1.17	1.28	1.37	1.44	1.47	1.46
-40	0.22	0.25	0.27	0.32	0.40	0.49	0.60	0.73	0.89	1.07	1.28	1.53	1.81	2.15	2.53	2.95	3.34	3.65	3.79
-30	0.22	0.26	0.29	0.36	0.46	0.58	0.74	0.94	1.19	1.49	1.87	2.40	3.13	4.20	5.81	8.12	11.0	13.9	15.7
-20	0.22	0.26	0.30	0.40	0.51	0.66	0.87	1.14	1.48	1.92	2.56	3.54	5.25	8.55	14.9	26.7	45.8	70.5	89.4
-10	0.22	0.26	0.31	0.41	0.55	0.73	0.97	1.29	1.70	2.27	3.13	4.57	7.37	13.3	27.3	64.3	153	294	433
0	0.22	0.26	0.32	0.42	0.56	0.76	1.02	1.36	1.81	2.42	3.30	4.70	6.99	11.0	19.5	42.2	98.9	236	452
10	0.22	0.26	0.32	0.42	0.56	0.76	1.01	1.35	1.78	2.37	3.21	4.55	6.74	10.6	18.4	35.5	72.7	138	198
20	0.22	0.26	0.31	0.42	0.55	0.72	0.95	1.25	1.63	2.11	2.76	3.69	5.11	7.26	10.6	16.1	23.7	32.2	37.8
30	0.22	0.26	0.30	0.39	0.51	0.65	0.84	1.08	1.37	1.73	2.17	2.73	3.44	4.37	5.55	6.94	8.41	9.74	10.5
40	0.22	0.26	0.29	0.36	0.45	0.57	0.71	0.88	1.09	1.34	1.61	1.92	2.28	2.67	3.08	3.50	3.89	4.19	4.36
50	0.22	0.25	0.28	0.33	0.39	0.48	0.58	0.69	0.83	0.98	1.14	1.32	1.50	1.68	1.86	2.02	2.16	2.26	2.32
60	0.22	0.24	0.27	0.30	0.34	0.39	0.46	0.53	0.60	0.68	0.77	0.86	0.95	1.05	1.13	1.21	1.27	1.32	1.35
70	0.22	0.24	0.26	0.28	0.30	0.32	0.36	0.39	0.43	0.47	0.51	0.55	0.59	0.63	0.67	0.70	0.73	0.75	0.77
80	0.22	0.23	0.24	0.25	0.27	0.29	0.29	0.31	0.32	0.34	0.35	0.36	0.38	0.39	0.40	0.41	0.43	0.43	0.44
90	0.22	0.22	0.23	0.23	0.24	0.24	0.25	0.25	0.26	0.26	0.27	0.27	0.28	0.28	0.29	0.30	0.30	0.31	0.31
100	0.22	0.22	0.21	0.21	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.23
110	0.22	0.21	0.21	0.21	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.19	0.20	0.20	0.19	0.19	0.19	0.19	0.19
120	0.22	0.20	0.20	0.20	0.20	0.20	0.19	0.19	0.20	0.20	0.21	0.21	0.22	0.23	0.23	0.22	0.23	0.23	0.22
130	0.22	0.20	0.20	0.19	0.19	0.19	0.20	0.21	0.23	0.25	0.28	0.33	0.38	0.42	0.45	0.48	0.49	0.50	0.49
140	0.22	0.20	0.19	0.19	0.19	0.20	0.22	0.25	0.31	0.38	0.47	0.55	0.62	0.68	0.72	0.74	0.75	0.76	0.77
150	0.22	0.20	0.19	0.19	0.20	0.21	0.26	0.33	0.43	0.55	0.66	0.74	0.77	0.79	0.81	0.83	0.84	0.86	0.87
160	0.22	0.20	0.19	0.19	0.20	0.23	0.30	0.41	0.55	0.68	0.77	0.80	0.81	0.82	0.83	0.85	0.88	0.90	0.92
170	0.22	0.20	0.19	0.19	0.20	0.25	0.34	0.48	0.63	0.75	0.80	0.80	0.80	0.81	0.82	0.80	0.76	0.74	0.78
180	0.22	0.20	0.19	0.19	0.20	0.26	0.36	0.51	0.67	0.79	0.81	0.80	0.79	0.78	0.75	0.68	0.57	0.57	0.57

H_b Range:-90 - 90DEGH_b Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW GREEN-20D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:20 DEG	DIA.:65MM	SERIAL No.:IES003424
MFR.:	SUR.:1	Shielding Angle:

Table--2

UNIT: cd

H(DEC) V(DEC)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.59	0.58	0.49	0.42	0.31	0.21	0.09	0.02	0.00	0.00	0.03	0.07	0.08	0.08	0.08	0.06	0.05	0.06	
-170	0.62	0.58	0.51	0.42	0.31	0.20	0.10	0.03	0.01	0.01	0.04	0.07	0.08	0.08	0.08	0.06	0.05	0.06	
-160	0.56	0.50	0.42	0.33	0.24	0.14	0.06	0.02	0.01	0.01	0.05	0.07	0.08	0.08	0.08	0.06	0.05	0.06	
-150	0.35	0.30	0.24	0.18	0.12	0.06	0.03	0.01	0.01	0.04	0.06	0.07	0.08	0.08	0.08	0.06	0.05	0.06	
-140	0.13	0.11	0.08	0.05	0.03	0.02	0.01	0.02	0.04	0.05	0.07	0.08	0.08	0.08	0.07	0.06	0.06	0.06	
-130	0.02	0.01	0.01	0.01	0.01	0.02	0.03	0.04	0.05	0.07	0.07	0.08	0.08	0.08	0.06	0.06	0.06	0.06	
-120	0.02	0.02	0.02	0.03	0.04	0.05	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.07	0.06	0.06	0.06	
-110	0.07	0.07	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.06	
-100	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	
-90	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.06	0.06	
-80	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.11	0.11	0.10	0.10	0.09	0.08	0.08	0.07	0.06	
-70	0.35	0.35	0.34	0.33	0.32	0.31	0.29	0.27	0.25	0.22	0.20	0.18	0.15	0.14	0.11	0.09	0.08	0.06	
-60	0.70	0.70	0.69	0.66	0.62	0.58	0.54	0.49	0.44	0.39	0.34	0.29	0.23	0.19	0.15	0.11	0.08	0.06	
-50	1.49	1.47	1.40	1.30	1.19	1.05	0.92	0.80	0.69	0.59	0.49	0.41	0.33	0.25	0.19	0.14	0.09	0.06	
-40	3.94	3.83	3.50	3.01	2.51	2.04	1.64	1.31	1.05	0.84	0.68	0.54	0.43	0.32	0.23	0.16	0.10	0.06	
-30	16.6	15.3	12.5	9.46	6.69	4.57	3.11	2.20	1.58	1.17	0.88	0.68	0.52	0.39	0.27	0.18	0.10	0.06	
-20	93.6	78.7	55.2	34.5	20.1	11.3	6.29	3.64	2.32	1.56	1.10	0.81	0.60	0.44	0.31	0.20	0.11	0.06	
-10	424	333	205	105	49.6	23.4	11.3	5.61	3.10	1.93	1.29	0.91	0.65	0.47	0.33	0.21	0.12	0.06	
0	587	551	370	179	75.9	32.9	14.8	6.86	3.54	2.12	1.38	0.95	0.68	0.49	0.34	0.21	0.12	0.06	
10	268	254	176	96.1	46.9	22.8	11.3	5.70	3.20	2.00	1.35	0.95	0.68	0.49	0.34	0.21	0.12	0.06	
20	55.3	56.6	44.6	30.2	18.8	11.1	6.44	3.84	2.50	1.71	1.21	0.88	0.65	0.47	0.33	0.21	0.12	0.06	
30	12.4	12.7	11.4	9.20	6.86	4.88	3.44	2.49	1.83	1.36	1.02	0.77	0.58	0.43	0.30	0.20	0.11	0.06	
40	4.49	4.38	4.05	3.55	3.02	2.50	2.04	1.64	1.31	1.04	0.83	0.65	0.50	0.38	0.27	0.18	0.11	0.06	
50	2.28	2.19	2.06	1.89	1.70	1.49	1.29	1.10	0.93	0.78	0.64	0.52	0.41	0.31	0.23	0.16	0.10	0.06	
60	1.31	1.26	1.19	1.11	1.02	0.93	0.83	0.73	0.64	0.56	0.47	0.39	0.32	0.25	0.20	0.14	0.10	0.06	
70	0.75	0.72	0.69	0.65	0.61	0.57	0.52	0.47	0.42	0.37	0.32	0.28	0.24	0.20	0.16	0.12	0.09	0.06	
80	0.43	0.41	0.40	0.38	0.36	0.34	0.31	0.29	0.27	0.25	0.22	0.20	0.17	0.15	0.13	0.10	0.09	0.06	
90	0.30	0.28	0.27	0.26	0.24	0.23	0.21	0.20	0.19	0.17	0.16	0.15	0.13	0.12	0.10	0.09	0.08	0.06	
100	0.22	0.21	0.20	0.19	0.19	0.18	0.16	0.16	0.15	0.14	0.13	0.12	0.11	0.11	0.10	0.08	0.07	0.06	
110	0.18	0.18	0.17	0.17	0.16	0.15	0.15	0.14	0.14	0.14	0.12	0.11	0.10	0.09	0.09	0.08	0.07	0.06	
120	0.21	0.19	0.18	0.17	0.16	0.15	0.14	0.14	0.13	0.13	0.12	0.11	0.11	0.09	0.08	0.07	0.07	0.06	
130	0.45	0.40	0.34	0.29	0.24	0.21	0.17	0.14	0.13	0.12	0.12	0.11	0.10	0.10	0.08	0.07	0.07	0.06	
140	0.69	0.61	0.53	0.46	0.38	0.29	0.22	0.17	0.13	0.12	0.11	0.11	0.10	0.09	0.09	0.07	0.06	0.06	
150	0.79	0.71	0.62	0.53	0.43	0.34	0.26	0.19	0.13	0.11	0.10	0.10	0.10	0.09	0.09	0.06	0.06	0.06	
160	0.84	0.75	0.66	0.55	0.45	0.34	0.24	0.17	0.12	0.08	0.09	0.10	0.09	0.09	0.08	0.06	0.06	0.06	
170	0.73	0.68	0.61	0.52	0.41	0.30	0.19	0.11	0.07	0.05	0.06	0.08	0.09	0.09	0.08	0.06	0.06	0.06	
180	0.59	0.58	0.49	0.42	0.31	0.21	0.09	0.02	0.00	0.00	0.03	0.07	0.08	0.08	0.08	0.06	0.05	0.06	

H_(b) Range:-90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks: