

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	2675.2 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	56.7V x 57.7H
	At 50% of Imax	29.2V x 29.7H
	At 90% of Imax	11.6V x 11.9H

Beam Flux	Total	1000.5 lumens per klm.
	To 10% of Imax	801.9 lumens per klm.
	To 50% of Imax	455.5 lumens per klm.
	To 90% of Imax	140.3 lumens per klm.

Upward LOR	1.8 %
Downward LOR	98.2 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:Astra D65-65mm-RGBW 6500K-30D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003431
MFR.:	SUR.:1	Shielding Angle:



DATA OF LAMP		Eff:61.92lm/W	
MODEL		Imax(cd)	397.5
NOMINAL POWER(W)	2.4	AVAILABILITY(%)	80.3
RATED VOLTAGE(V)	24	Avai. FLUX(lm)	119.4
NOMINAL FLUX(lm)	148.6	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	148.6
TEST VOLTAGE(V)	24	q @50%(H,V)	30,29DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm				F t	F a
	45	0.01	0.02	0.02	0.03	0.04	0.04	0.05	0.06	0.06	0.06	0.06	0.06	0.05	0.04	0.03	0.02	0.02	0.74	0.00		
	40	0.02	0.02	0.03	0.04	0.05	0.06	0.08	0.09	0.10	0.10	0.10	0.10	0.09	0.07	0.06	0.04	0.03	0.02	1.11	0.00	
	35	0.02	0.03	0.04	0.05	0.07	0.10	0.12	0.14	0.16	0.17	0.18	0.17	0.14	0.12	0.09	0.06	0.04	0.03	1.72	0.00	
	30	0.02	0.03	0.05	0.07	0.10	0.14	0.19	0.23	0.25	0.28	0.31	0.29	0.24	0.18	0.13	0.09	0.06	0.04	2.71	0.53	
	25	0.03	0.04	0.06	0.10	0.14	0.21	0.29	0.37	0.44	0.51	0.55	0.51	0.41	0.29	0.19	0.13	0.08	0.05	4.38	3.05	
	20	0.03	0.05	0.08	0.12	0.19	0.30	0.45	0.63	0.78	0.91	0.97	0.88	0.68	0.46	0.28	0.17	0.10	0.06	7.14	6.12	
	15	0.03	0.05	0.09	0.15	0.25	0.41	0.67	1.02	1.32	1.53	1.58	1.39	1.06	0.68	0.39	0.22	0.12	0.07	11.0	10.2	
		0.04	0.06	0.10	0.17	0.29	0.52	0.90	1.44	1.94	2.23	2.24	1.96	1.47	0.94	0.52	0.27	0.15	0.08	15.3	14.5	
		0.04	0.06	0.11	0.18	0.31	0.57	1.02	1.67	2.38	2.76	2.77	2.45	1.83	1.15	0.61	0.31	0.16	0.09	18.5	17.7	
		0.04	0.06	0.11	0.19	0.34	0.62	1.12	1.81	2.58	2.96	2.92	2.55	1.88	1.17	0.62	0.31	0.16	0.09	19.5	18.8	
		0.04	0.06	0.11	0.19	0.36	0.66	1.16	1.84	2.52	2.80	2.65	2.22	1.61	1.00	0.54	0.28	0.15	0.08	18.3	17.5	
	-15	0.04	0.06	0.10	0.18	0.32	0.58	0.99	1.52	2.04	2.25	2.09	1.72	1.23	0.76	0.42	0.23	0.13	0.07	14.7	13.9	
	-20	0.03	0.05	0.09	0.15	0.26	0.44	0.72	1.06	1.38	1.51	1.41	1.15	0.82	0.52	0.31	0.18	0.11	0.06	10.3	9.36	
	-25	0.03	0.04	0.07	0.12	0.19	0.30	0.46	0.64	0.81	0.88	0.82	0.68	0.50	0.33	0.21	0.13	0.08	0.05	6.35	5.29	
	-30	0.02	0.04	0.06	0.09	0.13	0.19	0.27	0.36	0.43	0.46	0.44	0.38	0.29	0.21	0.14	0.10	0.06	0.04	3.72	2.25	
-35	0.02	0.03	0.04	0.06	0.09	0.12	0.16	0.20	0.23	0.25	0.24	0.21	0.17	0.13	0.10	0.07	0.04	0.03	2.19	0.10		
-40	0.02	0.02	0.03	0.04	0.06	0.08	0.10	0.12	0.13	0.14	0.13	0.12	0.10	0.08	0.06	0.04	0.03	0.02	1.32	0.00		
-45	0.01	0.02	0.02	0.03	0.04	0.05	0.06	0.07	0.07	0.08	0.07	0.07	0.06	0.05	0.04	0.03	0.02	0.02	0.79	0.00		
	-45	-40	-35	-30	-25	-20	-15	-10	HORIZONTAL (DEG)				10	15	20	25	30	35	40	45		
F t	0.48	0.75	1.21	1.97	3.24	5.39	8.81	13.3	17.6	19.9	19.6	16.9	12.6	8.20	4.76	2.70	1.56	0.90	140	---		
F a	0.00	0.00	0.00	0.00	1.46	4.18	7.74	12.3	16.7	19.0	18.7	16.0	11.7	7.14	3.55	1.02	0.00	0.00	---	119		

one-half-peak spread: U:14.5,D:14.9 , L:14.7,R:15.2


NEMA Beam Type: Type 4

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:Astra D65-65mm-RGBW 6500K-30D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003431
MFR.:	SUR.:1	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:Astra D65-65mm-RGBW 6500K-30D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003431
MFR.:	SUR.:1	Shielding Angle:



H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME:Astra D65-65mm-RGBW 6500K-30D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003431
MFR.:	SUR.:1	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW 6500K-30D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003431
MFR.:	SUR.:1	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.38	0.36	0.36	0.36	0.39	0.46	0.58	0.72	0.87	0.99	1.08	1.10	1.10	1.08	1.05	0.98	0.92	0.89	0.93
-170	0.38	0.35	0.35	0.35	0.38	0.44	0.54	0.66	0.78	0.89	0.96	0.98	0.98	0.98	0.97	0.94	0.92	0.89	0.89
-160	0.38	0.35	0.35	0.35	0.36	0.41	0.47	0.57	0.66	0.75	0.82	0.85	0.85	0.85	0.84	0.84	0.83	0.81	0.78
-150	0.38	0.35	0.34	0.34	0.35	0.36	0.41	0.47	0.53	0.60	0.65	0.67	0.69	0.68	0.66	0.64	0.62	0.58	0.53
-140	0.38	0.35	0.34	0.33	0.33	0.34	0.35	0.38	0.42	0.45	0.48	0.49	0.49	0.48	0.46	0.42	0.39	0.33	0.26
-130	0.38	0.35	0.34	0.33	0.32	0.31	0.32	0.32	0.32	0.34	0.34	0.34	0.33	0.32	0.29	0.26	0.22	0.17	0.11
-120	0.38	0.35	0.34	0.33	0.31	0.30	0.30	0.29	0.28	0.28	0.26	0.25	0.23	0.22	0.20	0.18	0.15	0.12	0.09
-110	0.38	0.35	0.33	0.32	0.31	0.30	0.29	0.28	0.27	0.26	0.24	0.23	0.23	0.21	0.20	0.18	0.17	0.15	0.14
-100	0.38	0.36	0.34	0.32	0.31	0.29	0.28	0.27	0.26	0.25	0.24	0.23	0.22	0.20	0.19	0.18	0.17	0.16	0.14
-90	0.38	0.37	0.35	0.34	0.32	0.31	0.29	0.28	0.26	0.25	0.24	0.22	0.21	0.19	0.18	0.16	0.15	0.13	0.12
-80	0.38	0.39	0.38	0.37	0.36	0.35	0.35	0.34	0.34	0.35	0.35	0.36	0.36	0.36	0.36	0.35	0.35	0.34	0.33
-70	0.38	0.40	0.39	0.39	0.40	0.43	0.46	0.51	0.56	0.61	0.66	0.71	0.75	0.79	0.81	0.83	0.84	0.84	0.82
-60	0.38	0.40	0.41	0.43	0.49	0.58	0.68	0.79	0.91	1.03	1.15	1.26	1.37	1.47	1.54	1.60	1.64	1.65	1.64
-50	0.38	0.40	0.42	0.49	0.61	0.77	0.95	1.14	1.36	1.58	1.83	2.09	2.38	2.70	3.03	3.37	3.67	3.88	3.96
-40	0.38	0.41	0.45	0.57	0.75	0.98	1.25	1.54	1.90	2.32	2.84	3.55	4.50	5.78	7.38	9.12	10.8	12.2	13.0
-30	0.38	0.42	0.48	0.64	0.88	1.18	1.54	1.98	2.53	3.28	4.41	6.20	8.90	12.8	18.1	24.5	31.8	38.5	42.7
-20	0.38	0.42	0.50	0.70	1.00	1.36	1.82	2.39	3.17	4.37	6.40	9.82	15.5	24.7	39.6	62.8	93.8	127	150
-10	0.38	0.43	0.52	0.75	1.08	1.49	2.01	2.70	3.66	5.22	7.90	12.8	21.2	36.5	64.8	114	187	271	338
0	0.38	0.43	0.53	0.77	1.11	1.55	2.10	2.84	3.83	5.39	8.06	12.8	20.6	33.9	57.3	102	174	266	351
10	0.38	0.43	0.53	0.76	1.10	1.53	2.06	2.76	3.71	5.17	7.59	11.9	18.9	30.1	49.3	82.6	134	192	230
20	0.38	0.43	0.52	0.73	1.04	1.43	1.91	2.51	3.30	4.40	6.12	8.89	13.3	19.7	28.5	40.6	55.6	70.4	78.8
30	0.38	0.43	0.50	0.68	0.94	1.26	1.67	2.15	2.74	3.48	4.47	5.89	7.89	10.6	14.1	17.9	21.8	24.8	26.3
40	0.38	0.42	0.48	0.61	0.81	1.08	1.38	1.73	2.15	2.62	3.17	3.82	4.60	5.53	6.62	7.77	8.79	9.60	9.99
50	0.38	0.42	0.46	0.54	0.68	0.87	1.09	1.33	1.60	1.89	2.20	2.53	2.87	3.22	3.55	3.86	4.13	4.32	4.41
60	0.38	0.42	0.44	0.49	0.56	0.68	0.80	0.96	1.12	1.28	1.46	1.63	1.80	1.96	2.11	2.23	2.33	2.40	2.44
70	0.38	0.42	0.42	0.45	0.48	0.53	0.59	0.66	0.74	0.82	0.90	0.99	1.07	1.14	1.21	1.27	1.31	1.35	1.37
80	0.38	0.41	0.42	0.43	0.43	0.45	0.46	0.49	0.51	0.53	0.56	0.58	0.61	0.63	0.65	0.67	0.69	0.71	0.72
90	0.38	0.39	0.39	0.40	0.40	0.40	0.41	0.41	0.42	0.42	0.42	0.43	0.43	0.44	0.44	0.44	0.45	0.45	0.46
100	0.38	0.38	0.38	0.37	0.37	0.37	0.38	0.37	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38
110	0.38	0.37	0.36	0.37	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.36
120	0.38	0.36	0.36	0.36	0.36	0.36	0.36	0.36	0.37	0.38	0.39	0.40	0.41	0.42	0.45	0.45	0.45	0.44	0.44
130	0.38	0.36	0.36	0.36	0.36	0.36	0.37	0.39	0.42	0.46	0.50	0.55	0.59	0.64	0.67	0.70	0.71	0.72	0.72
140	0.38	0.36	0.36	0.36	0.36	0.38	0.41	0.45	0.52	0.60	0.68	0.76	0.83	0.89	0.93	0.97	0.99	1.00	1.00
150	0.38	0.36	0.36	0.36	0.37	0.40	0.46	0.54	0.65	0.76	0.86	0.95	1.02	1.07	1.09	1.12	1.13	1.14	1.15
160	0.38	0.36	0.36	0.36	0.38	0.43	0.52	0.63	0.75	0.89	0.99	1.06	1.09	1.11	1.13	1.14	1.15	1.16	1.18
170	0.38	0.36	0.36	0.36	0.39	0.45	0.56	0.69	0.83	0.96	1.06	1.09	1.10	1.11	1.10	1.08	1.05	1.04	1.07
180	0.38	0.36	0.36	0.36	0.39	0.46	0.58	0.72	0.87	0.99	1.08	1.10	1.10	1.08	1.05	0.98	0.92	0.89	0.94

H_(b) Range:-90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW 6500K-30D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003431
MFR.:	SUR.:1	Shielding Angle:

Table--2

UNIT: cd

H(°) \ V(°)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
-180	0.80	0.78	0.69	0.58	0.47	0.35	0.24	0.15	0.09	0.09	0.10	0.13	0.14	0.13	0.13	0.11	0.12	0.17
-170	0.84	0.78	0.70	0.59	0.47	0.36	0.23	0.15	0.10	0.10	0.11	0.13	0.14	0.13	0.13	0.11	0.12	0.17
-160	0.73	0.67	0.58	0.49	0.38	0.27	0.19	0.12	0.10	0.10	0.11	0.13	0.13	0.13	0.13	0.10	0.12	0.17
-150	0.50	0.45	0.38	0.31	0.24	0.18	0.13	0.11	0.10	0.11	0.12	0.13	0.14	0.13	0.13	0.10	0.12	0.17
-140	0.25	0.23	0.19	0.16	0.13	0.11	0.10	0.10	0.11	0.12	0.13	0.13	0.13	0.13	0.11	0.10	0.12	0.17
-130	0.11	0.11	0.10	0.10	0.10	0.10	0.10	0.11	0.12	0.12	0.13	0.13	0.14	0.13	0.11	0.10	0.13	0.17
-120	0.09	0.10	0.10	0.10	0.11	0.11	0.11	0.12	0.14	0.13	0.14	0.13	0.12	0.11	0.11	0.12	0.13	0.17
-110	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.13	0.13	0.12	0.12	0.12	0.11	0.11	0.12	0.12	0.14
-100	0.14	0.14	0.14	0.13	0.13	0.13	0.13	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.13	0.14	0.15
-90	0.12	0.12	0.13	0.13	0.13	0.14	0.14	0.14	0.14	0.15	0.15	0.15	0.16	0.16	0.16	0.17	0.17	0.17
-80	0.34	0.35	0.35	0.35	0.35	0.35	0.34	0.33	0.32	0.30	0.29	0.27	0.25	0.24	0.22	0.21	0.19	0.17
-70	0.84	0.84	0.83	0.82	0.79	0.76	0.72	0.68	0.63	0.57	0.51	0.46	0.41	0.35	0.30	0.25	0.21	0.17
-60	1.67	1.67	1.64	1.57	1.50	1.39	1.28	1.16	1.04	0.92	0.81	0.70	0.59	0.48	0.39	0.31	0.23	0.17
-50	4.08	4.03	3.81	3.48	3.08	2.67	2.28	1.94	1.64	1.39	1.16	0.96	0.79	0.63	0.48	0.36	0.25	0.17
-40	13.2	12.7	11.5	9.85	8.02	6.26	4.75	3.53	2.66	2.05	1.60	1.27	1.00	0.77	0.57	0.41	0.27	0.17
-30	43.4	40.1	33.9	26.8	20.2	14.7	10.3	6.89	4.56	3.06	2.16	1.60	1.21	0.91	0.66	0.45	0.29	0.17
-20	152	134	105	72.4	47.2	30.0	19.1	12.1	7.39	4.49	2.83	1.93	1.39	1.02	0.73	0.49	0.31	0.17
-10	336	298	234	160	94.2	52.5	29.8	17.6	10.3	5.91	3.46	2.21	1.54	1.10	0.78	0.52	0.32	0.17
0	395	385	317	221	130	68.0	36.2	20.6	11.9	6.66	3.78	2.35	1.60	1.14	0.80	0.53	0.32	0.17
10	258	245	203	144	87.9	50.1	28.8	17.3	10.3	5.96	3.52	2.27	1.57	1.12	0.79	0.52	0.32	0.17
20	95.2	95.7	82.4	61.4	42.1	27.7	18.2	11.8	7.42	4.61	2.95	2.02	1.46	1.06	0.76	0.51	0.31	0.17
30	29.7	30.0	27.3	22.9	18.1	13.7	9.94	6.95	4.76	3.27	2.33	1.72	1.29	0.96	0.69	0.48	0.30	0.17
40	10.7	10.7	10.1	9.09	7.77	6.36	5.02	3.86	2.96	2.29	1.79	1.40	1.09	0.84	0.62	0.44	0.28	0.17
50	4.52	4.48	4.31	4.00	3.60	3.16	2.72	2.31	1.95	1.63	1.35	1.10	0.89	0.70	0.53	0.39	0.26	0.17
60	2.42	2.36	2.27	2.14	1.99	1.83	1.65	1.47	1.30	1.13	0.97	0.82	0.68	0.56	0.44	0.34	0.25	0.17
70	1.35	1.32	1.27	1.22	1.15	1.08	1.00	0.91	0.83	0.75	0.66	0.58	0.50	0.43	0.36	0.29	0.23	0.17
80	0.71	0.69	0.67	0.65	0.62	0.60	0.57	0.53	0.50	0.47	0.43	0.39	0.35	0.31	0.28	0.25	0.21	0.17
90	0.44	0.42	0.41	0.39	0.38	0.36	0.34	0.33	0.31	0.30	0.28	0.27	0.25	0.23	0.22	0.20	0.19	0.17
100	0.37	0.35	0.34	0.32	0.30	0.29	0.28	0.26	0.25	0.23	0.22	0.22	0.20	0.19	0.18	0.17	0.17	0.17
110	0.34	0.33	0.32	0.30	0.29	0.28	0.27	0.25	0.24	0.23	0.21	0.19	0.18	0.16	0.16	0.16	0.16	0.17
120	0.42	0.39	0.37	0.35	0.31	0.28	0.26	0.25	0.24	0.22	0.21	0.20	0.18	0.16	0.14	0.15	0.15	0.17
130	0.67	0.60	0.54	0.48	0.41	0.36	0.31	0.27	0.24	0.22	0.21	0.19	0.18	0.16	0.14	0.12	0.14	0.17
140	0.92	0.83	0.73	0.63	0.54	0.45	0.37	0.31	0.25	0.22	0.20	0.19	0.17	0.16	0.14	0.12	0.13	0.17
150	1.06	0.96	0.86	0.74	0.63	0.51	0.40	0.32	0.26	0.22	0.19	0.18	0.17	0.16	0.15	0.12	0.13	0.17
160	1.08	0.99	0.88	0.78	0.65	0.52	0.40	0.29	0.24	0.19	0.17	0.17	0.16	0.15	0.14	0.11	0.12	0.17
170	0.98	0.92	0.83	0.72	0.60	0.48	0.34	0.24	0.18	0.15	0.14	0.15	0.15	0.14	0.14	0.11	0.12	0.17
180	0.80	0.78	0.69	0.58	0.47	0.35	0.24	0.15	0.09	0.09	0.10	0.13	0.14	0.13	0.13	0.11	0.12	0.17

H_(b) Range: -90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: HIGH

Temperature: 25.3DEG

Operators:

Test Date: 2025-02-06

V(B) Range: -180 - 180DEG

V(B) Interval: 0.5DEG

Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity: 65.0%

Test Distance: 8.630m [K=1.0000]

Remarks: