

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	2712.9 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	56.3V x 56.9H
	At 50% of Imax	29.1V x 29.5H
	At 90% of Imax	11.5V x 11.7H

Beam Flux	Total	1000.3 lumens per klm.
	To 10% of Imax	795.2 lumens per klm.
	To 50% of Imax	451.3 lumens per klm.
	To 90% of Imax	128.9 lumens per klm.

Upward LOR	2.1 %
Downward LOR	98.0 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:Astra D65-65mm-RGBW ALL-30D-Rev2	TYPE:RGBW W=6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003427
MFR.:	SUR.:1	Shielding Angle:



DATA OF LAMP		Eff:37.17lm/W	
MODEL		Imax(cd)	847.0
NOMINAL POWER(W)	8.4	AVAILABILITY(%)	79.6
RATED VOLTAGE(V)	24	Avai. FLUX(lm)	248.5
NOMINAL FLUX(lm)	312.2	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	312.2
TEST VOLTAGE(V)	24	q @50%(H,V)	29,29DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM														UNIT:lm				F t	F a	
	45	0.03	0.04	0.05	0.07	0.08	0.10	0.11	0.12	0.13	0.13	0.12	0.11	0.10	0.08	0.07	0.06	0.05	0.04	1.49	0.00
	40	0.04	0.05	0.07	0.09	0.11	0.14	0.17	0.19	0.20	0.21	0.20	0.18	0.15	0.12	0.09	0.07	0.06	0.04	2.18	0.00
	35	0.04	0.06	0.09	0.12	0.16	0.21	0.26	0.30	0.33	0.33	0.31	0.27	0.23	0.18	0.13	0.10	0.08	0.06	3.27	0.00
	30	0.05	0.07	0.11	0.16	0.23	0.31	0.40	0.48	0.54	0.54	0.50	0.42	0.34	0.26	0.20	0.15	0.11	0.07	4.94	0.24
	25	0.06	0.09	0.14	0.21	0.32	0.45	0.62	0.79	0.92	0.94	0.84	0.67	0.50	0.38	0.30	0.22	0.14	0.09	7.68	4.18
	20	0.06	0.10	0.16	0.26	0.42	0.65	0.98	1.36	1.65	1.71	1.48	1.11	0.81	0.65	0.46	0.30	0.19	0.12	12.5	9.99
	15	0.07	0.11	0.19	0.31	0.52	0.88	1.48	2.20	2.81	2.96	2.53	1.91	1.55	1.11	0.70	0.41	0.24	0.14	20.1	18.2
	10	0.07	0.12	0.21	0.35	0.60	1.08	1.93	3.08	4.14	4.46	3.93	3.39	2.62	1.73	0.99	0.54	0.30	0.17	29.7	28.0
	5	0.07	0.12	0.21	0.36	0.62	1.14	2.10	3.49	5.00	5.78	5.63	4.96	3.73	2.37	1.29	0.66	0.34	0.19	38.1	36.4
	0	0.08	0.13	0.22	0.39	0.72	1.37	2.54	4.24	5.95	6.27	6.23	5.46	4.06	2.53	1.36	0.68	0.35	0.19	42.8	41.2
	-5	0.08	0.13	0.24	0.44	0.85	1.67	3.06	4.82	5.76	5.94	5.67	4.78	3.49	2.16	1.18	0.61	0.33	0.18	41.4	39.8
	-10	0.07	0.13	0.23	0.43	0.81	1.57	2.77	3.87	4.54	4.74	4.47	3.71	2.66	1.65	0.93	0.51	0.28	0.16	33.5	31.9
	-15	0.07	0.12	0.21	0.37	0.67	1.19	1.89	2.57	3.02	3.18	3.01	2.49	1.79	1.14	0.68	0.40	0.23	0.13	23.2	21.4
	-20	0.06	0.10	0.17	0.29	0.50	0.78	1.12	1.48	1.72	1.82	1.75	1.46	1.09	0.75	0.48	0.30	0.18	0.11	14.2	12.0
	-25	0.05	0.08	0.13	0.22	0.34	0.48	0.64	0.80	0.91	0.96	0.93	0.81	0.64	0.48	0.33	0.22	0.14	0.08	8.24	5.13
	-30	0.04	0.06	0.10	0.15	0.22	0.29	0.37	0.44	0.49	0.51	0.50	0.46	0.38	0.30	0.22	0.15	0.10	0.06	4.85	0.08
-35	0.03	0.05	0.07	0.10	0.13	0.18	0.22	0.25	0.27	0.28	0.28	0.26	0.23	0.19	0.14	0.10	0.07	0.04	2.89	0.00	
-40	0.03	0.04	0.05	0.06	0.08	0.10	0.12	0.14	0.15	0.16	0.16	0.15	0.13	0.11	0.09	0.07	0.05	0.03	1.72	0.00	
-45	-45	-40	-35	-30	-25	-20	-15	-10	HORIZONTAL (DEG)				10	15	20	25	30	35	40	45	
F t	1.01	1.61	2.64	4.38	7.37	12.6	20.8	30.6	38.5	40.9	38.5	32.6	24.5	16.2	9.65	5.55	3.25	1.90	293	---	
F a	0.00	0.00	0.00	0.00	3.67	10.0	18.5	28.6	36.5	39.0	36.5	30.5	22.2	13.9	7.11	2.07	0.00	0.00	---	248	

one-half-peak spread: U:14.4,D:14.9 , L:15.4,R:14.4


NEMA Beam Type: Type 4

H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:Astra D65-65mm-RGBW ALL-30D-Rev2	TYPE:RGBW W=6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003427
MFR.:	SUR.:1	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:Astra D65-65mm-RGBW ALL-30D-Rev2	TYPE:RGBW W=6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003427
MFR.:	SUR.:1	Shielding Angle:



H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME:Astra D65-65mm-RGBW ALL-30D-Rev2	TYPE:RGBW W=6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003427
MFR.:	SUR.:1	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW ALL-30D-Rev2	TYPE:RGBW W=6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003427
MFR.:	SUR.:1	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.95	0.87	0.85	0.86	0.92	1.08	1.33	1.62	1.93	2.19	2.37	2.45	2.44	2.40	2.32	2.17	2.04	2.01	2.03
-170	0.95	0.86	0.83	0.83	0.88	0.99	1.17	1.38	1.60	1.77	1.89	1.94	1.96	1.96	1.94	1.91	1.87	1.91	1.93
-160	0.95	0.85	0.82	0.80	0.82	0.88	0.99	1.12	1.24	1.33	1.38	1.39	1.38	1.37	1.37	1.48	1.60	1.66	1.67
-150	0.95	0.85	0.80	0.78	0.77	0.78	0.82	0.87	0.91	0.92	0.89	0.83	0.75	0.74	0.87	1.00	1.09	1.14	1.15
-140	0.95	0.84	0.79	0.76	0.73	0.71	0.69	0.68	0.66	0.61	0.53	0.41	0.36	0.42	0.48	0.53	0.58	0.62	0.63
-130	0.95	0.84	0.78	0.74	0.70	0.66	0.63	0.58	0.52	0.44	0.34	0.29	0.29	0.30	0.30	0.31	0.31	0.30	0.30
-120	0.95	0.85	0.77	0.72	0.68	0.64	0.59	0.54	0.48	0.41	0.34	0.33	0.32	0.31	0.31	0.31	0.31	0.32	0.32
-110	0.95	0.85	0.78	0.71	0.66	0.62	0.57	0.52	0.48	0.42	0.40	0.40	0.40	0.40	0.40	0.40	0.41	0.41	0.42
-100	0.95	0.86	0.79	0.72	0.65	0.60	0.54	0.49	0.45	0.41	0.41	0.41	0.41	0.40	0.40	0.40	0.41	0.41	0.41
-90	0.95	0.88	0.81	0.74	0.68	0.61	0.54	0.47	0.41	0.34	0.34	0.35	0.36	0.36	0.37	0.37	0.38	0.39	0.39
-80	0.95	0.89	0.84	0.80	0.75	0.71	0.68	0.64	0.62	0.60	0.64	0.68	0.73	0.76	0.79	0.82	0.84	0.86	0.87
-70	0.95	0.91	0.89	0.87	0.87	0.90	0.96	1.02	1.10	1.18	1.29	1.41	1.52	1.62	1.71	1.77	1.83	1.86	1.87
-60	0.95	0.94	0.94	0.96	1.06	1.21	1.39	1.59	1.80	2.00	2.20	2.46	2.71	2.95	3.16	3.33	3.47	3.54	3.56
-50	0.95	0.96	0.98	1.10	1.32	1.60	1.93	2.29	2.68	3.10	3.56	4.14	4.82	5.58	6.36	7.09	7.70	8.08	8.17
-40	0.95	0.98	1.05	1.26	1.60	2.04	2.53	3.11	3.79	4.65	5.86	7.60	10.1	13.2	16.7	20.3	23.4	25.6	26.3
-30	0.95	1.00	1.11	1.42	1.88	2.46	3.15	4.01	5.13	6.82	9.64	14.4	21.7	32.3	44.4	58.0	71.7	82.3	86.5
-20	0.95	1.02	1.17	1.56	2.13	2.84	3.72	4.88	6.53	9.29	14.2	22.8	37.8	63.1	106	163	228	287	311
-10	0.95	1.04	1.22	1.66	2.30	3.12	4.15	5.52	7.53	10.8	16.9	28.1	48.5	87.1	164	309	523	654	710
0	0.95	1.05	1.24	1.71	2.40	3.26	4.37	5.80	7.79	10.7	15.9	25.1	40.3	65.8	111	200	357	555	737
10	0.95	1.05	1.24	1.70	2.37	3.23	4.32	5.72	7.65	10.5	15.5	24.3	38.7	62.1	103	178	293	413	491
20	0.95	1.05	1.22	1.64	2.25	3.04	4.02	5.27	6.89	9.25	12.9	19.0	28.5	42.3	62.1	88.2	120	150	166
30	0.95	1.04	1.18	1.53	2.05	2.73	3.55	4.55	5.78	7.38	9.59	12.8	17.5	23.8	31.1	39.0	46.8	52.8	55.6
40	0.95	1.03	1.13	1.40	1.80	2.34	2.97	3.72	4.59	5.60	6.81	8.31	10.1	12.1	14.5	16.9	19.0	20.6	21.3
50	0.95	1.02	1.09	1.26	1.54	1.91	2.36	2.87	3.45	4.07	4.75	5.47	6.20	6.94	7.65	8.33	8.89	9.26	9.42
60	0.95	1.00	1.07	1.14	1.30	1.52	1.79	2.10	2.44	2.81	3.18	3.55	3.90	4.24	4.54	4.80	5.01	5.16	5.24
70	0.95	0.99	1.03	1.08	1.13	1.23	1.34	1.48	1.64	1.81	1.98	2.16	2.33	2.48	2.63	2.74	2.84	2.90	2.95
80	0.95	0.96	1.00	1.03	1.05	1.08	1.11	1.13	1.17	1.21	1.26	1.31	1.36	1.40	1.45	1.49	1.52	1.55	1.57
90	0.95	0.96	0.97	0.97	0.98	0.99	1.00	1.01	1.02	1.03	1.03	1.03	1.03	1.03	1.03	1.03	1.03	1.03	1.03
100	0.95	0.93	0.93	0.93	0.93	0.92	0.92	0.92	0.92	0.91	0.90	0.89	0.88	0.87	0.87	0.87	0.86	0.85	0.85
110	0.95	0.92	0.91	0.89	0.88	0.88	0.88	0.87	0.87	0.86	0.86	0.85	0.85	0.85	0.85	0.85	0.86	0.86	0.86
120	0.95	0.91	0.88	0.87	0.87	0.86	0.86	0.86	0.87	0.87	0.89	0.93	0.97	1.01	1.05	1.07	1.09	1.09	1.09
130	0.95	0.90	0.87	0.86	0.86	0.86	0.88	0.91	0.97	1.05	1.15	1.25	1.36	1.45	1.54	1.60	1.65	1.66	1.66
140	0.95	0.89	0.86	0.86	0.86	0.89	0.95	1.05	1.20	1.36	1.53	1.70	1.85	1.98	2.09	2.17	2.22	2.25	2.25
150	0.95	0.88	0.86	0.85	0.88	0.94	1.06	1.24	1.46	1.69	1.91	2.10	2.24	2.35	2.43	2.49	2.54	2.57	2.59
160	0.95	0.87	0.86	0.85	0.90	1.00	1.18	1.42	1.69	1.96	2.17	2.34	2.44	2.49	2.52	2.54	2.55	2.56	2.58
170	0.95	0.87	0.85	0.86	0.91	1.05	1.28	1.55	1.86	2.12	2.31	2.43	2.47	2.48	2.46	2.39	2.32	2.26	2.28
180	0.95	0.87	0.85	0.86	0.92	1.08	1.33	1.62	1.93	2.19	2.37	2.45	2.44	2.40	2.32	2.17	2.04	2.01	2.04

H_(b) Range:-90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW ALL-30D-Rev2	TYPE:RGBW W=6500K	WEIGHT:
SPEC.:30 DEG	DIA.:65MM	SERIAL No.:IES003427
MFR.:	SUR.:1	Shielding Angle:

Table--2

UNIT: cd

H(°) \ V(°)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
-180	1.82	1.72	1.57	1.36	1.12	0.86	0.63	0.44	0.31	0.30	0.32	0.37	0.41	0.43	0.41	0.35	0.32	0.45
-170	1.85	1.75	1.59	1.38	1.12	0.86	0.62	0.44	0.33	0.30	0.32	0.36	0.41	0.43	0.41	0.35	0.32	0.45
-160	1.61	1.51	1.36	1.16	0.93	0.72	0.52	0.39	0.32	0.31	0.33	0.37	0.41	0.42	0.40	0.36	0.32	0.45
-150	1.11	1.03	0.92	0.78	0.64	0.50	0.39	0.33	0.31	0.32	0.34	0.39	0.41	0.42	0.39	0.35	0.33	0.45
-140	0.60	0.56	0.50	0.44	0.39	0.34	0.31	0.30	0.31	0.33	0.37	0.40	0.42	0.41	0.37	0.34	0.33	0.45
-130	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.31	0.35	0.37	0.39	0.41	0.41	0.39	0.37	0.33	0.34	0.45
-120	0.32	0.32	0.32	0.33	0.34	0.35	0.36	0.37	0.38	0.40	0.41	0.41	0.39	0.38	0.34	0.33	0.35	0.45
-110	0.42	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.42	0.41	0.40	0.39	0.37	0.35	0.33	0.34	0.37	0.45
-100	0.41	0.41	0.41	0.40	0.40	0.40	0.39	0.39	0.38	0.36	0.35	0.34	0.33	0.33	0.35	0.37	0.40	0.45
-90	0.39	0.38	0.38	0.37	0.36	0.36	0.35	0.35	0.34	0.35	0.37	0.38	0.39	0.40	0.41	0.42	0.44	0.45
-80	0.88	0.89	0.89	0.89	0.87	0.85	0.83	0.80	0.77	0.73	0.70	0.66	0.62	0.58	0.54	0.50	0.47	0.45
-70	1.90	1.91	1.89	1.86	1.81	1.74	1.65	1.56	1.44	1.32	1.20	1.07	0.95	0.83	0.71	0.61	0.51	0.45
-60	3.64	3.66	3.60	3.48	3.31	3.10	2.86	2.60	2.34	2.08	1.82	1.58	1.34	1.12	0.91	0.72	0.56	0.45
-50	8.60	8.65	8.31	7.67	6.82	5.93	5.09	4.31	3.64	3.08	2.58	2.15	1.77	1.42	1.12	0.84	0.61	0.45
-40	27.7	27.4	25.4	22.2	18.4	14.5	10.8	7.90	5.90	4.50	3.53	2.80	2.22	1.73	1.31	0.95	0.66	0.45
-30	90.5	85.7	74.3	60.4	46.6	34.0	23.6	15.6	10.1	6.75	4.74	3.51	2.66	2.02	1.49	1.05	0.69	0.45
-20	320	287	225	160	105	67.3	43.0	27.1	16.4	9.84	6.21	4.22	3.06	2.26	1.63	1.13	0.72	0.45
-10	712	642	507	347	206	115	65.3	38.6	22.6	12.9	7.56	4.82	3.37	2.43	1.73	1.18	0.74	0.45
0	840	823	682	477	280	148	78.2	44.5	25.6	14.4	8.22	5.10	3.50	2.50	1.77	1.20	0.75	0.45
10	466	364	318	242	158	95.2	57.0	34.9	21.1	12.5	7.60	4.94	3.47	2.50	1.77	1.21	0.75	0.45
20	158	132	97.0	74.2	62.9	47.0	33.1	22.4	14.7	9.57	6.40	4.46	3.26	2.39	1.71	1.18	0.75	0.45
30	54.0	49.0	41.8	34.1	26.7	21.6	17.0	12.9	9.50	6.96	5.14	3.87	2.93	2.20	1.60	1.12	0.73	0.45
40	21.0	19.8	17.8	15.4	13.0	10.8	9.19	7.73	6.34	5.10	4.07	3.23	2.53	1.94	1.45	1.04	0.70	0.45
50	9.35	9.07	8.60	7.97	7.29	6.59	5.90	5.20	4.48	3.79	3.16	2.59	2.09	1.65	1.28	0.95	0.67	0.45
60	5.22	5.13	4.97	4.75	4.50	4.20	3.88	3.56	3.15	2.74	2.35	1.99	1.66	1.36	1.09	0.84	0.63	0.45
70	2.95	2.92	2.87	2.79	2.69	2.57	2.43	2.28	2.10	1.88	1.67	1.47	1.27	1.09	0.91	0.74	0.58	0.45
80	1.57	1.57	1.56	1.55	1.52	1.49	1.45	1.42	1.37	1.28	1.18	1.06	0.96	0.86	0.75	0.65	0.55	0.45
90	1.03	1.04	1.04	1.04	1.04	1.04	1.05	1.05	1.05	0.98	0.92	0.85	0.78	0.71	0.65	0.58	0.51	0.45
100	0.85	0.86	0.86	0.87	0.88	0.89	0.90	0.91	0.92	0.86	0.80	0.74	0.68	0.62	0.57	0.52	0.47	0.45
110	0.85	0.85	0.84	0.84	0.83	0.83	0.83	0.84	0.82	0.78	0.73	0.68	0.63	0.58	0.52	0.47	0.44	0.45
120	1.08	1.05	1.02	0.98	0.94	0.90	0.85	0.83	0.79	0.75	0.70	0.66	0.61	0.56	0.50	0.44	0.42	0.45
130	1.64	1.60	1.53	1.44	1.34	1.23	1.12	0.97	0.83	0.73	0.68	0.64	0.60	0.54	0.49	0.43	0.39	0.45
140	2.23	2.19	2.11	2.01	1.87	1.70	1.45	1.17	0.93	0.77	0.67	0.61	0.57	0.54	0.47	0.41	0.38	0.45
150	2.57	2.53	2.47	2.39	2.27	1.97	1.59	1.26	0.98	0.78	0.65	0.58	0.54	0.51	0.46	0.41	0.36	0.45
160	2.58	2.59	2.58	2.49	2.16	1.81	1.47	1.15	0.89	0.70	0.58	0.52	0.51	0.49	0.44	0.39	0.35	0.45
170	2.34	2.43	2.25	2.01	1.72	1.43	1.12	0.86	0.65	0.53	0.47	0.45	0.46	0.46	0.43	0.37	0.33	0.45
180	1.82	1.72	1.57	1.36	1.12	0.86	0.63	0.44	0.31	0.30	0.32	0.37	0.41	0.43	0.41	0.35	0.32	0.45

H_b Range:-90 - 90DEGH_b Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks: