

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	1443.2 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	84.5V x 81.8H
	At 50% of Imax	43.9V x 43.6H
	At 90% of Imax	18.9V x 17.8H

Beam Flux	Total	999.9 lumens per klm.
	To 10% of Imax	892.2 lumens per klm.
	To 50% of Imax	499.0 lumens per klm.
	To 90% of Imax	135.1 lumens per klm.

Upward LOR	0.0 %
Downward LOR	100.0 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:Astra D65-65mm-RGBW BLUE-40D-Rev2	TYPE:RGBW-BLUE	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003441
MFR.:	SUR.:1	Shielding Angle:



DATA OF LAMP		Eff:6.32lm/W	
MODEL		Imax(cd)	21.88
NOMINAL POWER(W)	2.4	AVAILABILITY(%)	89.1
RATED VOLTAGE(V)	24	Avai. FLUX(lm)	13.51
NOMINAL FLUX(lm)	15.16	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	15.16
TEST VOLTAGE(V)	24	q @50%(H,V)	44,44DEG

		AREA FLUX DIAGRAM																UNIT:lm				F t	F a
		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00			
VERTICAL (DEG)	72	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.07	0.00			
	64	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.13	0.00			
	56	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.03	0.04	0.03	0.03	0.02	0.01	0.01	0.00	0.00	0.26	0.03			
	48	0.00	0.00	0.00	0.01	0.01	0.02	0.04	0.05	0.07	0.07	0.07	0.06	0.04	0.02	0.01	0.01	0.00	0.49	0.35			
	40	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.10	0.12	0.14	0.13	0.10	0.07	0.04	0.02	0.01	0.00	0.85	0.76			
	32	0.00	0.00	0.00	0.01	0.02	0.05	0.10	0.16	0.21	0.24	0.22	0.16	0.10	0.06	0.03	0.01	0.00	1.38	1.31			
	24	0.00	0.00	0.00	0.01	0.03	0.07	0.13	0.23	0.32	0.35	0.31	0.24	0.15	0.08	0.04	0.01	0.00	1.97	1.91			
		0.00	0.00	0.00	0.01	0.03	0.07	0.15	0.26	0.37	0.41	0.38	0.29	0.18	0.09	0.04	0.02	0.00	2.32	2.26			
		0.00	0.00	0.00	0.01	0.03	0.07	0.15	0.26	0.37	0.41	0.38	0.29	0.18	0.09	0.04	0.02	0.00	2.33	2.27			
		0.00	0.00	0.00	0.01	0.03	0.07	0.14	0.23	0.32	0.35	0.32	0.24	0.15	0.08	0.04	0.01	0.00	2.01	1.95			
	-24	0.00	0.00	0.00	0.01	0.03	0.06	0.11	0.17	0.23	0.25	0.23	0.17	0.11	0.06	0.03	0.01	0.00	1.47	1.40			
	-32	0.00	0.00	0.00	0.01	0.02	0.04	0.07	0.11	0.14	0.15	0.14	0.11	0.07	0.04	0.02	0.01	0.00	0.93	0.84			
	-40	0.00	0.00	0.00	0.01	0.01	0.02	0.04	0.06	0.08	0.08	0.07	0.06	0.04	0.02	0.01	0.00	0.00	0.52	0.40			
	-48	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.04	0.04	0.03	0.02	0.01	0.01	0.00	0.00	0.25	0.05			
	-56	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.10	0.00			
	-64	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00			
-72	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00				
		-72	-64	-56	-48	-40	-32	-24	-16	HORIZONTAL (DEG)				16	24	32	40	48	56	64	72		
F t	0.01	0.02	0.05	0.11	0.26	0.55	1.04	1.73	2.36	2.59	2.36	1.81	1.16	0.62	0.30	0.12	0.04	0.01	15	---			
F a	0.00	0.00	0.00	0.00	0.06	0.42	0.93	1.63	2.26	2.49	2.26	1.72	1.06	0.52	0.15	0.00	0.00	0.00	---	14			

one-half-peak spread: U:23.9,D:20.3 , L:23.0,R:20.9


NEMA Beam Type: Type 5

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:Astra D65-65mm-RGBW BLUE-40D-Rev2	TYPE:RGBW-BLUE	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003441
MFR.:	SUR.:1	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:Astra D65-65mm-RGBW BLUE-40D-Rev2	TYPE:RGBW-BLUE	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003441
MFR.:	SUR.:1	Shielding Angle:



H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME:Astra D65-65mm-RGBW BLUE-40D-Rev2	TYPE:RGBW-BLUE	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003441
MFR.:	SUR.:1	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW BLUE-40D-Rev2	TYPE:RGBW-BLUE	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003441
MFR.:	SUR.:1	Shielding Angle:

Table--1

UNIT: cd

H(DEC) V(DEC)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.03
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.05	0.08	0.10	0.13	0.14	0.16	0.19	0.20	0.21	0.22
-50	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.07	0.11	0.15	0.20	0.26	0.34	0.43	0.54	0.65	0.75	0.84	0.89
-40	0.00	0.00	0.00	0.00	0.01	0.04	0.09	0.14	0.20	0.28	0.41	0.58	0.83	1.15	1.53	1.93	2.33	2.65	2.86
-30	0.00	0.00	0.00	0.00	0.02	0.07	0.13	0.20	0.30	0.46	0.72	1.13	1.71	2.45	3.36	4.33	5.30	6.11	6.65
-20	0.00	0.00	0.00	0.00	0.05	0.11	0.17	0.27	0.41	0.65	1.08	1.76	2.76	4.08	5.72	7.66	9.74	11.6	12.8
-10	0.00	0.00	0.00	0.00	0.05	0.13	0.19	0.30	0.47	0.76	1.29	2.17	3.46	5.23	7.73	10.9	14.4	17.4	19.4
0	0.00	0.00	0.00	0.00	0.06	0.13	0.20	0.30	0.46	0.73	1.22	2.08	3.27	5.02	7.62	11.2	15.2	18.4	20.5
10	0.00	0.00	0.00	0.01	0.06	0.14	0.21	0.31	0.48	0.76	1.26	2.09	3.30	4.98	7.43	10.6	14.3	17.4	19.4
20	0.00	0.00	0.00	0.01	0.06	0.13	0.19	0.29	0.43	0.67	1.06	1.67	2.57	3.75	5.22	7.04	9.00	10.8	11.9
30	0.00	0.00	0.00	0.01	0.04	0.09	0.16	0.24	0.35	0.50	0.74	1.11	1.63	2.26	3.03	3.84	4.63	5.30	5.73
40	0.00	0.00	0.00	0.01	0.02	0.07	0.12	0.18	0.25	0.35	0.48	0.63	0.86	1.15	1.48	1.83	2.15	2.42	2.59
50	0.00	0.00	0.00	0.00	0.01	0.03	0.08	0.11	0.17	0.22	0.28	0.36	0.44	0.54	0.64	0.74	0.85	0.93	0.99
60	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.06	0.09	0.12	0.16	0.19	0.23	0.27	0.30	0.33	0.36	0.38	0.40
70	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.06	0.08	0.10	0.11	0.13	0.14	0.16	0.17	0.18
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.04	0.04
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

H_(b) Range:-90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW BLUE-40D-Rev2	TYPE:RGBW-BLUE	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003441
MFR.:	SUR.:1	Shielding Angle:

Table--2

UNIT: cd

H(DEC) V(DEC)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.04	0.04	0.05	0.05	0.04	0.04	0.04	0.03	0.03	0.03	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.23	0.23	0.23	0.21	0.19	0.18	0.15	0.12	0.10	0.08	0.06	0.04	0.03	0.01	0.00	0.00	0.00	0.00	
-50	0.92	0.90	0.84	0.75	0.64	0.52	0.41	0.32	0.24	0.18	0.14	0.09	0.06	0.04	0.01	0.00	0.00	0.00	
-40	2.90	2.80	2.57	2.25	1.87	1.47	1.09	0.77	0.52	0.35	0.24	0.16	0.11	0.06	0.02	0.00	0.00	0.00	
-30	6.78	6.51	5.88	5.02	4.08	3.19	2.36	1.63	1.05	0.64	0.39	0.24	0.15	0.09	0.04	0.01	0.00	0.00	
-20	13.0	12.5	11.2	9.43	7.42	5.49	3.95	2.73	1.75	1.03	0.57	0.33	0.19	0.11	0.05	0.01	0.00	0.00	
-10	19.4	18.5	16.7	14.1	11.1	8.05	5.50	3.73	2.40	1.39	0.75	0.41	0.23	0.13	0.06	0.02	0.00	0.00	
0	21.6	21.4	19.6	16.8	13.3	9.54	6.39	4.23	2.72	1.59	0.84	0.45	0.25	0.14	0.07	0.02	0.00	0.00	
10	19.5	18.4	16.4	13.8	10.9	7.89	5.42	3.70	2.40	1.40	0.76	0.42	0.24	0.14	0.06	0.02	0.00	0.00	
20	12.2	11.7	10.6	8.93	7.08	5.30	3.86	2.72	1.76	1.05	0.60	0.35	0.21	0.12	0.06	0.01	0.00	0.00	
30	5.97	5.85	5.40	4.69	3.89	3.10	2.34	1.65	1.09	0.68	0.43	0.27	0.17	0.10	0.05	0.01	0.00	0.00	
40	2.67	2.63	2.47	2.21	1.87	1.50	1.14	0.84	0.59	0.41	0.28	0.19	0.13	0.07	0.03	0.00	0.00	0.00	
50	1.01	0.99	0.94	0.85	0.74	0.62	0.51	0.40	0.32	0.24	0.18	0.13	0.08	0.05	0.01	0.00	0.00	0.00	
60	0.40	0.39	0.37	0.34	0.32	0.28	0.24	0.20	0.17	0.13	0.10	0.07	0.04	0.02	0.00	0.00	0.00	0.00	
70	0.18	0.16	0.16	0.15	0.13	0.12	0.11	0.09	0.07	0.06	0.04	0.02	0.01	0.00	0.00	0.00	0.00	0.00	
80	0.04	0.04	0.03	0.03	0.03	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H_(b) Range:-90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks: