

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	1459.6 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	83.0V x 80.3H
	At 50% of Imax	42.7V x 42.3H
	At 90% of Imax	18.5V x 17.4H

Beam Flux	Total	1000.3 lumens per klm.
	To 10% of Imax	860.3 lumens per klm.
	To 50% of Imax	478.6 lumens per klm.
	To 90% of Imax	120.4 lumens per klm.

Upward LOR	1.7 %
Downward LOR	98.3 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:Astra D65-65mm-RGBW GREEN-40D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003440
MFR.:	SUR.:1	Shielding Angle:



DATA OF LAMP		Eff:44.76lm/W	
MODEL		Imax(cd)	156.8
NOMINAL POWER(W)	2.4	AVAILABILITY(%)	85.9
RATED VOLTAGE(V)	24	Avai. FLUX(lm)	92.24
NOMINAL FLUX(lm)	107.4	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	107.4
TEST VOLTAGE(V)	24	q @50%(H,V)	42,43DEG

		AREA FLUX DIAGRAM														UNIT:lm				F t	F a	
		0.00	0.01	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.01	0.01	0.00	0.33	0.00	
VERTICAL (DEG)	72	0.00	0.01	0.01	0.02	0.03	0.03	0.04	0.05	0.06	0.06	0.05	0.05	0.04	0.03	0.02	0.01	0.01	0.00	0.53	0.00	
	64	0.00	0.01	0.02	0.03	0.04	0.05	0.07	0.09	0.10	0.11	0.10	0.09	0.07	0.05	0.03	0.02	0.01	0.01	0.89	0.00	
	56	0.01	0.01	0.02	0.03	0.06	0.09	0.13	0.18	0.22	0.24	0.23	0.19	0.13	0.09	0.05	0.03	0.01	0.01	1.71	0.08	
	48	0.01	0.01	0.03	0.05	0.08	0.15	0.25	0.36	0.44	0.48	0.45	0.37	0.26	0.16	0.08	0.04	0.02	0.01	3.23	2.20	
	40	0.01	0.02	0.03	0.06	0.12	0.24	0.42	0.64	0.82	0.91	0.85	0.66	0.44	0.26	0.13	0.05	0.02	0.01	5.68	4.97	
	32	0.01	0.02	0.04	0.07	0.16	0.35	0.65	1.06	1.46	1.62	1.46	1.10	0.69	0.38	0.18	0.07	0.03	0.01	9.35	8.78	
	24	0.01	0.02	0.04	0.08	0.20	0.44	0.88	1.58	2.28	2.48	2.17	1.60	0.97	0.50	0.24	0.09	0.03	0.01	13.6	13.1	
	-24	0.01	0.02	0.04	0.08	0.21	0.47	1.00	1.87	2.69	2.94	2.65	1.99	1.21	0.60	0.27	0.10	0.03	0.01	16.2	15.7	
		0.01	0.02	0.04	0.08	0.21	0.49	1.02	1.88	2.69	2.94	2.66	2.01	1.22	0.60	0.27	0.10	0.03	0.01	16.3	15.8	
		0.01	0.02	0.04	0.08	0.21	0.47	0.94	1.64	2.30	2.51	2.22	1.66	1.00	0.51	0.24	0.09	0.03	0.01	14.0	13.5	
		0.01	0.02	0.03	0.07	0.17	0.38	0.72	1.18	1.61	1.76	1.57	1.17	0.72	0.39	0.19	0.07	0.03	0.01	10.1	9.56	
		-32	0.01	0.01	0.03	0.06	0.13	0.26	0.48	0.74	0.97	1.05	0.95	0.72	0.47	0.27	0.13	0.05	0.02	0.01	6.33	5.67
		-40	0.01	0.01	0.02	0.04	0.08	0.16	0.27	0.41	0.52	0.56	0.51	0.40	0.27	0.16	0.08	0.04	0.02	0.01	3.55	2.63
		-48	0.00	0.01	0.02	0.03	0.05	0.08	0.13	0.19	0.24	0.26	0.24	0.19	0.13	0.08	0.04	0.02	0.01	0.01	1.76	0.22
		-56	0.00	0.01	0.01	0.02	0.03	0.04	0.06	0.08	0.09	0.10	0.10	0.08	0.06	0.04	0.03	0.02	0.01	0.01	0.80	0.00
	-64	0.00	0.01	0.01	0.01	0.02	0.03	0.03	0.04	0.04	0.04	0.04	0.04	0.03	0.02	0.02	0.01	0.01	0.00	0.40	0.00	
-72	0.00	0.00	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.00	0.00	0.22	0.00		
		-72	-64	-56	-48	-40	-32	-24	-16	HORIZONTAL (DEG)				16	24	32	40	48	56	64	72	
F t	0.10	0.23	0.44	0.85	1.81	3.78	7.14	12.0	16.6	18.1	16.3	12.3	7.76	4.17	2.02	0.84	0.33	0.14	105	---		
F a	0.00	0.00	0.00	0.00	0.26	2.77	6.29	11.3	15.9	17.4	15.6	11.6	7.00	3.33	0.89	0.00	0.00	0.00	---	92		

one-half-peak spread: U:21.9,D:21.1 , L:21.2,R:21.4


NEMA Beam Type: Type 5

H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:Astra D65-65mm-RGBW GREEN-40D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003440
MFR.:	SUR.:1	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:Astra D65-65mm-RGBW GREEN-40D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003440
MFR.:	SUR.:1	Shielding Angle:



H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(b) Range: -90 - 90DEG
H(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators:
Test Date: 2025-02-06

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME:Astra D65-65mm-RGBW GREEN-40D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003440
MFR.:	SUR.:1	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:
Test Date:2025-02-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW GREEN-40D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003440
MFR.:	SUR.:1	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.30	0.30	0.30	0.31	0.34	0.38	0.44	0.51	0.59	0.66	0.71	0.72	0.72	0.72	0.71	0.68	0.64	0.63	0.65
-170	0.30	0.30	0.29	0.30	0.32	0.36	0.41	0.47	0.54	0.59	0.64	0.65	0.65	0.65	0.65	0.63	0.60	0.57	0.59
-160	0.30	0.29	0.29	0.29	0.30	0.33	0.38	0.42	0.47	0.51	0.55	0.57	0.57	0.57	0.56	0.56	0.55	0.53	0.50
-150	0.30	0.29	0.28	0.28	0.29	0.30	0.33	0.36	0.39	0.42	0.45	0.47	0.48	0.47	0.46	0.44	0.43	0.40	0.37
-140	0.30	0.29	0.28	0.27	0.27	0.28	0.29	0.31	0.32	0.34	0.35	0.36	0.36	0.35	0.34	0.32	0.29	0.27	0.23
-130	0.30	0.29	0.28	0.27	0.26	0.26	0.25	0.26	0.26	0.26	0.26	0.26	0.26	0.25	0.22	0.21	0.18	0.15	0.11
-120	0.30	0.29	0.27	0.26	0.25	0.24	0.23	0.23	0.22	0.21	0.20	0.20	0.18	0.17	0.16	0.14	0.11	0.09	0.07
-110	0.30	0.28	0.27	0.26	0.25	0.23	0.22	0.21	0.20	0.19	0.18	0.16	0.15	0.14	0.12	0.11	0.09	0.07	0.06
-100	0.30	0.28	0.27	0.26	0.24	0.23	0.22	0.20	0.19	0.18	0.16	0.15	0.14	0.13	0.11	0.10	0.09	0.07	0.06
-90	0.30	0.28	0.27	0.25	0.24	0.22	0.21	0.20	0.18	0.17	0.15	0.14	0.12	0.11	0.09	0.08	0.07	0.05	0.04
-80	0.30	0.28	0.27	0.25	0.24	0.23	0.23	0.23	0.24	0.24	0.24	0.24	0.25	0.26	0.27	0.27	0.27	0.27	0.26
-70	0.30	0.28	0.27	0.27	0.29	0.31	0.34	0.39	0.46	0.52	0.58	0.64	0.70	0.75	0.80	0.84	0.86	0.87	0.86
-60	0.30	0.28	0.29	0.31	0.36	0.45	0.56	0.69	0.83	0.97	1.11	1.26	1.40	1.55	1.68	1.81	1.91	1.98	2.01
-50	0.30	0.29	0.31	0.36	0.48	0.64	0.84	1.05	1.29	1.56	1.87	2.26	2.74	3.31	4.00	4.68	5.33	5.88	6.21
-40	0.30	0.29	0.33	0.43	0.62	0.86	1.14	1.46	1.86	2.40	3.16	4.27	5.86	7.95	10.5	13.1	15.8	18.0	19.5
-30	0.30	0.30	0.35	0.50	0.74	1.05	1.42	1.89	2.54	3.55	5.16	7.77	11.5	16.6	22.7	29.6	36.1	41.9	45.7
-20	0.30	0.30	0.37	0.56	0.86	1.22	1.67	2.28	3.20	4.72	7.39	11.8	18.4	27.7	39.1	52.8	67.8	80.8	89.7
-10	0.30	0.31	0.38	0.60	0.92	1.33	1.84	2.53	3.57	5.37	8.60	14.3	23.4	35.6	53.2	76.0	102	124	138
0	0.30	0.31	0.39	0.63	0.95	1.36	1.89	2.56	3.53	5.12	8.06	13.6	22.2	33.9	52.4	78.1	109	134	148
10	0.30	0.31	0.39	0.62	0.95	1.37	1.89	2.58	3.59	5.30	8.34	13.7	22.1	33.6	50.4	73.5	100	124	138
20	0.30	0.31	0.38	0.59	0.90	1.30	1.78	2.40	3.28	4.69	7.11	11.0	16.9	25.0	35.2	47.3	61.0	73.2	81.0
30	0.30	0.31	0.37	0.54	0.81	1.15	1.56	2.07	2.73	3.67	5.12	7.41	10.6	14.9	20.0	25.6	30.9	35.4	38.3
40	0.30	0.30	0.36	0.48	0.69	0.97	1.30	1.68	2.13	2.69	3.41	4.43	5.79	7.58	9.75	12.0	14.1	15.8	17.0
50	0.30	0.30	0.35	0.41	0.56	0.76	1.00	1.27	1.57	1.91	2.28	2.70	3.18	3.72	4.32	4.96	5.57	6.06	6.37
60	0.30	0.30	0.32	0.37	0.44	0.56	0.71	0.88	1.07	1.27	1.48	1.69	1.90	2.12	2.32	2.51	2.67	2.79	2.88
70	0.30	0.30	0.31	0.33	0.37	0.41	0.48	0.56	0.65	0.75	0.86	0.97	1.07	1.17	1.26	1.34	1.41	1.47	1.51
80	0.30	0.30	0.31	0.31	0.32	0.33	0.35	0.38	0.40	0.42	0.45	0.48	0.52	0.55	0.58	0.61	0.64	0.66	0.68
90	0.30	0.30	0.30	0.31	0.31	0.31	0.32	0.32	0.32	0.33	0.33	0.33	0.34	0.34	0.34	0.35	0.35	0.35	0.36
100	0.30	0.30	0.30	0.30	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31
110	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.29
120	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.31	0.31	0.32	0.32	0.33	0.33	0.33	0.34	0.34	0.34	0.34	0.33
130	0.30	0.30	0.30	0.30	0.30	0.31	0.32	0.33	0.34	0.36	0.39	0.40	0.43	0.45	0.46	0.47	0.47	0.47	0.46
140	0.30	0.30	0.30	0.30	0.31	0.32	0.34	0.37	0.40	0.44	0.48	0.51	0.55	0.57	0.60	0.61	0.64	0.64	0.64
150	0.30	0.30	0.30	0.30	0.32	0.34	0.37	0.42	0.47	0.52	0.57	0.62	0.66	0.68	0.69	0.71	0.71	0.72	0.72
160	0.30	0.30	0.30	0.30	0.32	0.36	0.41	0.46	0.52	0.59	0.65	0.69	0.70	0.71	0.73	0.73	0.77	0.78	0.79
170	0.30	0.30	0.30	0.31	0.33	0.37	0.43	0.49	0.57	0.64	0.69	0.71	0.72	0.72	0.74	0.72	0.72	0.74	0.76
180	0.30	0.30	0.30	0.31	0.34	0.38	0.44	0.51	0.59	0.66	0.71	0.72	0.72	0.72	0.71	0.68	0.64	0.63	0.68

H_(b) Range: -90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature: 25.3DEG

Operators:

Test Date: 2025-02-06

V(B) Range: -180 - 180DEG

V(B) Interval: 0.5DEG

Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity: 65.0%

Test Distance: 8.630m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D65-65mm-RGBW GREEN-40D-Rev2	TYPE:RGBW-GREEN	WEIGHT:
SPEC.:40 DEG	DIA.:65MM	SERIAL No.:IES003440
MFR.:	SUR.:1	Shielding Angle:

Table--2

UNIT: cd

H(°) V(°)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.52	0.48	0.42	0.36	0.29	0.22	0.15	0.10	0.06	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.11	
-170	0.51	0.47	0.43	0.37	0.30	0.22	0.16	0.10	0.07	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.11	
-160	0.47	0.43	0.38	0.32	0.25	0.20	0.15	0.09	0.07	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.11	
-150	0.35	0.31	0.28	0.23	0.19	0.14	0.10	0.08	0.06	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.11	
-140	0.21	0.19	0.17	0.14	0.11	0.09	0.07	0.06	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.11	
-130	0.11	0.10	0.09	0.08	0.08	0.07	0.06	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.05	0.11	
-120	0.07	0.06	0.06	0.06	0.05	0.05	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.11	
-110	0.06	0.06	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.05	0.08	0.11	
-100	0.06	0.06	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.05	0.06	0.08	0.09	0.11	
-90	0.04	0.04	0.05	0.05	0.06	0.06	0.06	0.07	0.07	0.08	0.08	0.08	0.09	0.09	0.10	0.10	0.10	0.11	
-80	0.27	0.28	0.29	0.29	0.30	0.29	0.28	0.27	0.25	0.24	0.22	0.20	0.19	0.17	0.15	0.14	0.12	0.11	
-70	0.89	0.90	0.90	0.88	0.84	0.81	0.76	0.70	0.64	0.58	0.51	0.44	0.37	0.31	0.24	0.19	0.14	0.11	
-60	2.06	2.07	2.02	1.93	1.80	1.66	1.50	1.34	1.18	1.03	0.88	0.73	0.60	0.47	0.35	0.25	0.17	0.11	
-50	6.39	6.27	5.90	5.31	4.58	3.83	3.12	2.53	2.04	1.66	1.35	1.09	0.86	0.65	0.48	0.32	0.19	0.11	
-40	19.7	18.9	17.3	15.2	12.6	9.99	7.50	5.39	3.81	2.71	1.99	1.49	1.13	0.84	0.59	0.38	0.22	0.11	
-30	46.3	44.2	39.8	33.7	27.4	21.2	15.8	11.0	7.17	4.53	2.91	1.98	1.41	1.01	0.70	0.44	0.24	0.11	
-20	90.8	86.3	76.7	63.8	49.6	36.5	26.2	18.2	11.8	7.02	4.09	2.52	1.68	1.16	0.78	0.49	0.25	0.11	
-10	138	130	116	96.9	75.0	53.5	36.4	24.6	16.0	9.49	5.22	3.00	1.89	1.27	0.85	0.52	0.27	0.11	
0	155	151	136	115	89.9	63.5	42.0	27.9	18.1	10.7	5.80	3.23	1.99	1.32	0.88	0.54	0.27	0.11	
10	138	129	113	94.1	73.0	52.3	35.7	24.4	15.9	9.51	5.28	3.05	1.93	1.30	0.86	0.53	0.27	0.11	
20	83.2	79.4	71.2	59.8	47.0	35.0	25.4	18.0	11.8	7.10	4.22	2.63	1.75	1.21	0.81	0.50	0.26	0.11	
30	39.9	38.9	35.8	31.0	25.7	20.4	15.4	10.9	7.29	4.72	3.09	2.12	1.51	1.08	0.74	0.46	0.25	0.11	
40	17.5	17.2	16.2	14.5	12.3	9.92	7.66	5.63	4.10	2.98	2.20	1.66	1.25	0.92	0.64	0.41	0.23	0.11	
50	6.57	6.51	6.17	5.64	4.98	4.28	3.57	2.94	2.39	1.94	1.56	1.25	0.97	0.73	0.53	0.35	0.21	0.11	
60	2.88	2.83	2.72	2.56	2.37	2.16	1.93	1.71	1.48	1.27	1.07	0.88	0.71	0.55	0.41	0.29	0.19	0.11	
70	1.49	1.46	1.41	1.34	1.26	1.18	1.08	0.98	0.88	0.77	0.67	0.57	0.47	0.38	0.30	0.23	0.16	0.11	
80	0.67	0.65	0.63	0.60	0.58	0.55	0.52	0.48	0.44	0.40	0.36	0.32	0.29	0.25	0.21	0.17	0.14	0.11	
90	0.34	0.33	0.31	0.30	0.29	0.27	0.26	0.25	0.23	0.22	0.20	0.19	0.18	0.16	0.15	0.14	0.12	0.11	
100	0.29	0.28	0.26	0.25	0.23	0.22	0.21	0.19	0.18	0.16	0.15	0.13	0.12	0.11	0.10	0.11	0.11	0.11	
110	0.28	0.26	0.25	0.23	0.22	0.20	0.19	0.17	0.16	0.15	0.13	0.12	0.11	0.10	0.09	0.08	0.09	0.11	
120	0.31	0.29	0.26	0.24	0.22	0.20	0.18	0.17	0.15	0.14	0.13	0.11	0.10	0.09	0.08	0.07	0.07	0.11	
130	0.43	0.39	0.35	0.31	0.28	0.24	0.20	0.18	0.15	0.13	0.12	0.10	0.09	0.08	0.07	0.06	0.06	0.11	
140	0.59	0.54	0.46	0.40	0.34	0.29	0.23	0.19	0.16	0.13	0.11	0.09	0.08	0.07	0.06	0.06	0.05	0.11	
150	0.66	0.60	0.54	0.46	0.39	0.33	0.25	0.20	0.15	0.13	0.10	0.08	0.07	0.07	0.06	0.05	0.05	0.11	
160	0.72	0.65	0.55	0.48	0.40	0.33	0.26	0.19	0.14	0.11	0.09	0.07	0.06	0.06	0.05	0.05	0.05	0.11	
170	0.67	0.59	0.53	0.46	0.37	0.29	0.22	0.16	0.11	0.08	0.07	0.06	0.05	0.05	0.04	0.04	0.04	0.11	
180	0.52	0.48	0.42	0.36	0.29	0.22	0.15	0.10	0.06	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.11	

H_(b) Range: -90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature:25.3DEG

Operators:

Test Date:2025-02-06

V(B) Range: -180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks: