

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	5456.7 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	40.5V x 40.7H
	At 50% of Imax	21.1V x 20.6H
	At 90% of Imax	8.6V x 8.4H

Beam Flux	Total	1000.3 lumens per klm.
	To 10% of Imax	775.5 lumens per klm.
	To 50% of Imax	417.7 lumens per klm.
	To 90% of Imax	95.5 lumens per klm.

Upward LOR	2.0 %
Downward LOR	98.0 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-07-31

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:Astra D88-88mm-RGBW 6500K-20D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:20 DEG	DIA.:88MM	SERIAL No.:IES001368
MFR.:	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:31.34lm/W	
MODEL		Imax(cd)	1100
NOMINAL POWER(W)	6.432	AVAILABILITY(%)	77.4
RATED VOLTAGE(V)	48	Avai. FLUX(lm)	156.1
NOMINAL FLUX(lm)	201.6	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	201.6
TEST VOLTAGE(V)	48	q @50%(H,V)	21,21DEG

		AREA FLUX DIAGRAM															UNIT:lm				F t	F a
		0.03	0.04	0.05	0.07	0.08	0.10	0.11	0.13	0.14	0.14	0.14	0.13	0.11	0.10	0.08	0.06	0.05	0.04	1.60	0.00	
VERTICAL (DEG)	27	0.04	0.05	0.07	0.09	0.11	0.13	0.16	0.19	0.21	0.21	0.19	0.17	0.14	0.11	0.08	0.06	0.05	0.05	2.27	0.00	
	24	0.05	0.06	0.09	0.11	0.15	0.19	0.24	0.29	0.32	0.34	0.32	0.29	0.25	0.20	0.15	0.11	0.08	0.06	3.31	0.99	
	21	0.06	0.08	0.11	0.15	0.21	0.28	0.36	0.45	0.51	0.54	0.52	0.46	0.37	0.29	0.21	0.15	0.11	0.07	4.93	3.41	
	18	0.07	0.09	0.13	0.19	0.28	0.40	0.55	0.71	0.84	0.90	0.87	0.75	0.57	0.41	0.29	0.20	0.13	0.09	7.48	6.25	
	15	0.08	0.11	0.16	0.25	0.37	0.56	0.81	1.09	1.32	1.43	1.38	1.15	0.85	0.58	0.39	0.26	0.17	0.11	11.1	10.0	
	12	0.09	0.13	0.20	0.30	0.47	0.74	1.11	1.55	1.90	2.07	1.98	1.61	1.16	0.78	0.51	0.33	0.20	0.13	15.3	14.3	
	9	0.09	0.14	0.22	0.36	0.57	0.90	1.37	1.94	2.41	2.63	2.48	2.04	1.52	1.03	0.65	0.40	0.24	0.14	19.1	18.4	
	6	0.10	0.15	0.24	0.39	0.63	1.02	1.56	2.16	2.69	2.95	2.82	2.43	1.85	1.24	0.77	0.45	0.27	0.15	21.8	21.0	
	3	0.10	0.15	0.24	0.40	0.67	1.09	1.67	2.33	2.81	2.96	2.88	2.51	1.91	1.28	0.78	0.46	0.27	0.15	22.7	21.9	
	0	0.09	0.14	0.24	0.39	0.66	1.09	1.65	2.19	2.57	2.72	2.61	2.25	1.70	1.14	0.70	0.41	0.24	0.14	20.9	20.1	
-9	0.08	0.13	0.21	0.35	0.57	0.92	1.34	1.76	2.10	2.22	2.10	1.79	1.35	0.92	0.57	0.34	0.21	0.12	17.1	16.3		
	0.07	0.11	0.17	0.28	0.44	0.67	0.96	1.26	1.52	1.60	1.49	1.25	0.95	0.66	0.42	0.27	0.16	0.10	12.4	11.5		
	0.06	0.09	0.14	0.21	0.31	0.45	0.62	0.82	0.97	1.02	0.95	0.80	0.62	0.44	0.30	0.20	0.12	0.08	8.19	7.13		
	0.04	0.07	0.10	0.15	0.21	0.29	0.39	0.49	0.57	0.60	0.56	0.48	0.38	0.28	0.20	0.14	0.09	0.06	5.11	3.70		
	0.03	0.05	0.07	0.10	0.14	0.19	0.24	0.30	0.34	0.35	0.33	0.29	0.23	0.18	0.13	0.10	0.07	0.04	3.18	1.07		
	0.03	0.04	0.05	0.07	0.09	0.12	0.15	0.18	0.20	0.21	0.20	0.17	0.14	0.11	0.09	0.06	0.05	0.03	2.01	0.00		
-24	0.02	0.03	0.04	0.05	0.06	0.08	0.10	0.11	0.13	0.13	0.12	0.11	0.09	0.07	0.06	0.04	0.03	0.02	1.29	0.00		
	-27	-24	-21	-18	-15	-12	-9	-6	HORIZONTAL (DEG)				6	9	12	15	18	21	24	27		
F t	1.12	1.67	2.53	3.89	6.02	9.21	13.4	17.9	21.6	23.0	22.0	18.7	14.2	9.84	6.41	4.06	2.55	1.60	180	---		
F a	0.00	0.00	0.00	2.21	4.71	8.08	12.4	17.0	20.7	22.1	21.1	17.8	13.2	8.70	5.15	2.48	0.34	0.00	---	156		

one-half-peak spread: U:10.6,D:10.6 , L:10.5,R:10.3


NEMA Beam Type: Type 3

H_(b) Range: -90 - 90DEG
 H_(b) Interval: 0.5DEG
 Test Speed: LOW
 Temperature: 25.3DEG
 Operators: Fan
 Test Date: 2023-07-31

V(B) Range: -180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 8.630m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME:Astra D88-88mm-RGBW 6500K-20D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:20 DEG	DIA.:88MM	SERIAL No.:IES001368
MFR.:	SUR.:	Shielding Angle:




H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-07-31

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:Astra D88-88mm-RGBW 6500K-20D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:20 DEG	DIA.: 88MM	SERIAL No.:IES001368
MFR.:	SUR.:	Shielding Angle:



H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-07-31

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

Planar Illuminance Curve




H_b Range: -90 - 90DEG
H_b Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-07-31

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

AAI CURVES

NAME:Astra D88-88mm-RGBW 6500K-20D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:20 DEG	DIA.:88MM	SERIAL No.:IES001368
MFR.:	SUR.:	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range: -90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature: 25.3DEG
Operators: Fan
Test Date: 2023-07-31

V(B) Range: -180 - 180DEG
V(B) Interval: 0.5DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D88-88mm-RGBW 6500K-20D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:20 DEG	DIA.:88MM	SERIAL No.:IES001368
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.55	0.48	0.44	0.44	0.45	0.48	0.59	0.81	1.10	1.39	1.59	1.65	1.65	1.64	1.60	1.54	1.39	1.23	1.30
-170	0.55	0.47	0.43	0.42	0.42	0.43	0.49	0.63	0.82	1.00	1.13	1.20	1.23	1.27	1.30	1.29	1.32	1.36	1.34
-160	0.55	0.47	0.42	0.41	0.40	0.38	0.38	0.43	0.51	0.59	0.63	0.66	0.71	0.88	1.04	1.16	1.25	1.31	1.34
-150	0.55	0.46	0.41	0.40	0.38	0.34	0.31	0.28	0.27	0.24	0.22	0.32	0.44	0.56	0.68	0.78	0.87	0.92	0.95
-140	0.55	0.46	0.41	0.39	0.37	0.33	0.27	0.21	0.14	0.12	0.13	0.15	0.20	0.25	0.31	0.38	0.44	0.48	0.49
-130	0.55	0.47	0.41	0.38	0.36	0.33	0.29	0.22	0.17	0.14	0.13	0.12	0.12	0.12	0.12	0.13	0.15	0.17	0.18
-120	0.55	0.47	0.42	0.37	0.35	0.33	0.30	0.27	0.25	0.24	0.22	0.20	0.19	0.18	0.15	0.14	0.13	0.13	0.12
-110	0.55	0.49	0.43	0.39	0.35	0.32	0.30	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.28	0.27	0.26	0.25	0.25
-100	0.55	0.50	0.44	0.40	0.36	0.32	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.30	0.30	0.30	0.30
-90	0.55	0.50	0.46	0.41	0.36	0.31	0.26	0.25	0.24	0.24	0.23	0.23	0.22	0.23	0.24	0.24	0.25	0.26	0.27
-80	0.55	0.52	0.48	0.42	0.36	0.29	0.20	0.19	0.18	0.18	0.18	0.17	0.18	0.18	0.17	0.17	0.17	0.17	0.17
-70	0.55	0.54	0.50	0.45	0.38	0.29	0.20	0.17	0.18	0.20	0.23	0.27	0.31	0.34	0.35	0.37	0.38	0.38	0.38
-60	0.55	0.55	0.53	0.49	0.43	0.36	0.28	0.25	0.33	0.41	0.50	0.59	0.67	0.74	0.80	0.86	0.89	0.92	0.93
-50	0.55	0.57	0.58	0.55	0.52	0.51	0.51	0.50	0.57	0.72	0.87	1.04	1.21	1.38	1.56	1.72	1.87	1.97	2.02
-40	0.55	0.59	0.62	0.63	0.67	0.74	0.82	0.90	0.94	1.11	1.39	1.75	2.19	2.69	3.27	3.92	4.56	5.08	5.35
-30	0.55	0.62	0.67	0.73	0.84	1.01	1.21	1.42	1.64	1.85	2.18	3.01	4.18	5.83	8.14	11.3	15.6	19.7	22.2
-20	0.55	0.64	0.72	0.83	1.03	1.30	1.65	2.06	2.54	3.18	4.11	5.55	8.06	13.9	24.9	42.5	66.6	96.2	116
-10	0.55	0.66	0.77	0.93	1.20	1.58	2.08	2.71	3.53	4.75	6.64	9.97	16.5	30.9	64.5	138	280	472	620
0	0.55	0.67	0.81	1.02	1.34	1.81	2.44	3.27	4.39	6.07	8.80	13.6	22.8	41.8	85.8	187	412	772	1057
10	0.55	0.67	0.81	1.01	1.32	1.77	2.38	3.17	4.22	5.76	8.17	12.3	19.6	33.6	61.1	119	232	408	544
20	0.55	0.67	0.80	0.98	1.26	1.66	2.20	2.88	3.74	4.90	6.58	9.17	13.2	19.9	30.5	46.7	69.6	94.5	110
30	0.55	0.66	0.78	0.93	1.16	1.48	1.92	2.46	3.10	3.89	4.92	6.30	8.22	10.8	14.1	18.1	22.4	26.3	28.5
40	0.55	0.65	0.75	0.88	1.05	1.29	1.60	1.98	2.44	2.96	3.56	4.25	5.08	6.04	7.07	8.16	9.15	9.95	10.4
50	0.55	0.63	0.73	0.82	0.94	1.09	1.29	1.53	1.82	2.14	2.49	2.85	3.23	3.62	4.00	4.33	4.63	4.85	4.96
60	0.55	0.62	0.69	0.76	0.83	0.93	1.04	1.17	1.31	1.47	1.65	1.83	2.02	2.20	2.37	2.52	2.64	2.72	2.77
70	0.55	0.60	0.65	0.70	0.75	0.80	0.85	0.90	0.96	1.01	1.08	1.14	1.21	1.28	1.35	1.41	1.46	1.50	1.53
80	0.55	0.58	0.62	0.64	0.67	0.70	0.73	0.75	0.76	0.77	0.78	0.79	0.80	0.82	0.84	0.86	0.88	0.90	0.91
90	0.55	0.57	0.58	0.59	0.60	0.61	0.62	0.62	0.62	0.61	0.61	0.61	0.60	0.61	0.63	0.64	0.65	0.66	0.67
100	0.55	0.56	0.54	0.54	0.53	0.53	0.52	0.52	0.50	0.49	0.48	0.47	0.46	0.46	0.47	0.47	0.48	0.48	0.49
110	0.55	0.53	0.51	0.50	0.48	0.47	0.47	0.46	0.45	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
120	0.55	0.51	0.49	0.46	0.46	0.45	0.45	0.44	0.44	0.44	0.44	0.45	0.46	0.48	0.49	0.49	0.49	0.49	0.48
130	0.55	0.50	0.46	0.45	0.45	0.44	0.44	0.44	0.44	0.47	0.52	0.59	0.67	0.75	0.81	0.86	0.90	0.91	0.90
140	0.55	0.49	0.45	0.45	0.44	0.44	0.44	0.46	0.52	0.62	0.78	0.94	1.10	1.24	1.35	1.42	1.46	1.47	1.46
150	0.55	0.48	0.45	0.44	0.44	0.44	0.47	0.54	0.69	0.90	1.12	1.32	1.48	1.59	1.68	1.73	1.74	1.74	1.72
160	0.55	0.48	0.44	0.44	0.44	0.46	0.52	0.66	0.89	1.16	1.39	1.55	1.66	1.72	1.78	1.83	1.85	1.85	1.86
170	0.55	0.48	0.44	0.44	0.45	0.47	0.56	0.76	1.04	1.32	1.53	1.64	1.69	1.73	1.76	1.79	1.74	1.68	1.74
180	0.55	0.48	0.44	0.44	0.45	0.48	0.59	0.81	1.10	1.39	1.59	1.65	1.65	1.64	1.60	1.54	1.39	1.23	1.34

H_(b) Range:-90 - 90DEG
H_(b) Interval: 0.5DEG
Test Speed: LOW
Temperature:25.3DEG
Operators:Fan
Test Date:2023-07-31

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:8.630m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:Astra D88-88mm-RGBW 6500K-20D-Rev2	TYPE:RGBW-6500K	WEIGHT:
SPEC.:20 DEG	DIA.:88MM	SERIAL No.:IES001368
MFR.:	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H(°) \ V(°)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
-180	1.22	1.22	1.17	1.05	0.91	0.71	0.51	0.32	0.18	0.12	0.14	0.18	0.26	0.29	0.29	0.28	0.24	0.16
-170	1.34	1.29	1.24	1.11	0.92	0.71	0.50	0.31	0.17	0.13	0.13	0.18	0.25	0.29	0.29	0.28	0.24	0.16
-160	1.29	1.20	1.07	0.93	0.76	0.58	0.39	0.25	0.15	0.13	0.14	0.19	0.27	0.29	0.29	0.28	0.24	0.16
-150	0.90	0.82	0.70	0.59	0.47	0.35	0.24	0.17	0.13	0.13	0.15	0.22	0.28	0.29	0.29	0.27	0.23	0.16
-140	0.46	0.41	0.34	0.26	0.20	0.15	0.13	0.12	0.12	0.13	0.20	0.26	0.28	0.29	0.29	0.27	0.23	0.16
-130	0.17	0.15	0.14	0.12	0.12	0.12	0.13	0.14	0.17	0.21	0.25	0.28	0.29	0.29	0.28	0.27	0.22	0.16
-120	0.13	0.14	0.15	0.17	0.20	0.21	0.23	0.25	0.27	0.28	0.28	0.29	0.29	0.29	0.28	0.25	0.21	0.16
-110	0.26	0.27	0.28	0.29	0.29	0.30	0.29	0.29	0.29	0.30	0.29	0.29	0.29	0.29	0.28	0.27	0.23	0.16
-100	0.30	0.30	0.30	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.27	0.25	0.23	0.22	0.19	0.16
-90	0.25	0.24	0.23	0.22	0.21	0.20	0.20	0.21	0.21	0.22	0.22	0.23	0.21	0.20	0.19	0.18	0.17	0.16
-80	0.17	0.17	0.17	0.17	0.17	0.17	0.16	0.16	0.15	0.15	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16
-70	0.39	0.39	0.38	0.37	0.35	0.33	0.29	0.26	0.21	0.18	0.15	0.15	0.14	0.14	0.15	0.15	0.15	0.16
-60	0.93	0.91	0.89	0.84	0.78	0.71	0.63	0.55	0.46	0.37	0.29	0.22	0.17	0.15	0.14	0.14	0.15	0.16
-50	2.01	1.93	1.81	1.65	1.48	1.31	1.13	0.95	0.79	0.64	0.50	0.38	0.28	0.19	0.16	0.14	0.14	0.16
-40	5.23	4.84	4.25	3.61	3.02	2.46	1.97	1.56	1.23	0.96	0.75	0.57	0.40	0.27	0.18	0.14	0.14	0.16
-30	20.7	17.1	13.0	9.51	6.92	4.98	3.58	2.56	1.85	1.36	1.01	0.75	0.53	0.35	0.21	0.15	0.14	0.16
-20	108	81.1	54.4	32.3	17.9	10.2	6.29	4.04	2.66	1.81	1.28	0.91	0.64	0.42	0.25	0.16	0.14	0.16
-10	572	396	210	99.4	44.8	20.1	10.0	5.71	3.44	2.21	1.49	1.04	0.72	0.47	0.28	0.16	0.14	0.16
0	1064	768	390	166	68.8	28.5	12.7	6.65	3.84	2.40	1.59	1.10	0.76	0.49	0.29	0.17	0.14	0.16
10	533	350	187	95.8	47.8	23.9	12.8	7.52	4.62	2.99	2.02	1.39	0.94	0.61	0.36	0.21	0.15	0.16
20	107	88.1	61.4	39.2	24.9	16.4	10.7	6.97	4.64	3.19	2.22	1.55	1.05	0.68	0.41	0.25	0.17	0.16
30	27.8	24.8	20.8	16.5	12.8	9.73	7.43	5.71	4.19	3.05	2.20	1.56	1.08	0.71	0.44	0.27	0.19	0.16
40	10.3	9.79	8.95	7.92	6.78	5.72	4.80	4.01	3.35	2.68	2.00	1.45	1.02	0.69	0.45	0.30	0.20	0.16
50	4.94	4.82	4.59	4.29	3.94	3.54	3.15	2.77	2.40	2.06	1.68	1.25	0.92	0.65	0.46	0.32	0.21	0.16
60	2.76	2.72	2.63	2.51	2.37	2.20	2.02	1.83	1.64	1.46	1.30	1.06	0.81	0.61	0.45	0.33	0.23	0.16
70	1.53	1.51	1.47	1.43	1.37	1.31	1.24	1.17	1.11	1.04	0.98	0.89	0.72	0.58	0.45	0.33	0.23	0.16
80	0.90	0.90	0.89	0.87	0.86	0.85	0.84	0.83	0.82	0.81	0.81	0.79	0.67	0.55	0.44	0.33	0.24	0.16
90	0.67	0.66	0.66	0.65	0.65	0.64	0.65	0.66	0.67	0.68	0.69	0.69	0.60	0.52	0.43	0.34	0.25	0.16
100	0.48	0.48	0.48	0.47	0.48	0.48	0.49	0.51	0.52	0.54	0.57	0.58	0.54	0.48	0.42	0.35	0.26	0.16
110	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.45	0.46	0.48	0.49	0.47	0.44	0.40	0.34	0.27	0.16
120	0.48	0.48	0.47	0.47	0.46	0.45	0.45	0.44	0.44	0.44	0.45	0.44	0.42	0.41	0.38	0.34	0.27	0.16
130	0.89	0.86	0.81	0.75	0.67	0.60	0.53	0.47	0.44	0.44	0.43	0.41	0.39	0.38	0.37	0.34	0.26	0.16
140	1.45	1.42	1.36	1.27	1.13	0.98	0.81	0.66	0.54	0.44	0.40	0.39	0.37	0.36	0.35	0.32	0.26	0.16
150	1.73	1.72	1.69	1.63	1.52	1.38	1.18	0.95	0.67	0.46	0.36	0.35	0.36	0.34	0.33	0.31	0.26	0.16
160	1.85	1.84	1.81	1.75	1.68	1.59	1.30	0.96	0.65	0.44	0.32	0.30	0.33	0.33	0.32	0.30	0.25	0.16
170	1.73	1.77	1.79	1.65	1.44	1.22	0.98	0.71	0.47	0.32	0.24	0.24	0.29	0.31	0.31	0.30	0.25	0.16
180	1.22	1.22	1.17	1.05	0.91	0.71	0.51	0.32	0.18	0.12	0.14	0.18	0.26	0.29	0.29	0.28	0.24	0.16

H_(b) Range:-90 - 90DEGH_(b) Interval: 0.5DEG

Test Speed: LOW

Temperature:25.3DEG

Operators:Fan

Test Date:2023-07-31

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE G0-2000B_V1 SYSTEM V2.0.351

Humidity:65.0%

Test Distance:8.630m [K=1.0000]

Remarks: