

Test report

Light measurement results

Laboratory and Equipment

Test lab
Spectrometer Manufacturer and Model
Measurement date

n/a - serial: n/a sensor serial: n/a
n/a, n/a – n/a
5/5/2025

Measurement Conditions

Tested c-planes
Tested gamma angles
Input Power

9 – distance {C_PLANES_DIST}°
361 – {H_PLANES_DIST}°
11.6 W

Tested Light Source
Luminaire
Basic Luminous Shape
Item No.
Manufacturer


Blazeline Max-598mm-TW-1800K-15D-Rev1
NONE
Luminoscape

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity
Correlated Color Temperature, CCT
Color Rendering Index

713 lm – 2.29% / 97.71%
61 lm/W
6805 cd
1800 K
CRI 70.0


Polar light distribution diagram



Test report


Light measurement results

Beam details



Luminaire budgetary diagram


LAMPS (number of lamps)




Test report

Light measurement results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)



Test report


Light measurement results

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U2 G0



Forward Light

Low (0-30°)	284	lm	39.8%
Medium (30-60°)	27.6	lm	3.9%
High (60-80°)	3.1	lm	0.4%
Very High	0.7	lm	0.1%

Back Light

Low (0-30°)	331.4	lm	46.5%
Medium (30-60°)	42	lm	5.9%
High (60-80°)	6.5	lm	0.9%
Very High	1.6	lm	0.2%

Uplight

Low (90-100°)	2	lm	0.3%
High (100-180°)	14.4	lm	2%

Total

Sum	713	lm	100%
-----	-----	----	------