

Test report

Light measurement results

Laboratory and Equipment

Test lab

Spectrometer Manufacturer and Model

Measurement date

7/17/2025

Measurement Conditions

Tested c-planes

25 – distance {C_PLANES_DIST}°

Tested gamma angles

181 – {H_PLANES_DIST}°

Input Power

72.0 W

Tested Light Source

Luminaire

AuroRing-254mm-RGBW 4000K-LumiMax-35D

Basic Luminous Shape

NONE

Item No.

Manufacturer

Luminoscape

Main Light Measurement Results

Output – Total Lumen

4896 lm

Efficiency

68 lm/W

Peak Intensity

8961 cd


Correlated Color Temperature, CCT

4000 K

Color Rendering Index

CRI 85.0


Polar light distribution diagram



Test report


Light measurement results

Beam details



Luminaire budgetary diagram


LAMPS (number of lamps)




Test report

Light measurement results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)



Test report


Light measurement results

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B3 U0 G0



Forward Light

Low (0-30°)	1676.4 lm	34.2%
Medium (30-60°)	595.8 lm	12.2%
High (60-80°)	86.7 lm	1.8%
Very High	1.9 lm	0%

Back Light

Low (0-30°)	1787.2 lm	36.5%
Medium (30-60°)	650.1 lm	13.3%
High (60-80°)	95.1 lm	1.9%
Very High	2.9 lm	0.1%

Uplight

Low (90-100°)	0 lm	0%
High (100-180°)	0 lm	0%

Total

Sum	4896 lm	100%
-----	---------	------