

Test report

Light measurement results

Laboratory and Equipment

Test lab

Spectrometer Manufacturer and Model

Measurement date

7/17/2025

Measurement Conditions

Tested c-planes

25 – distance {C_PLANES_DIST}°

Tested gamma angles

181 – {H_PLANES_DIST}°

Input Power

71.5 W

Tested Light Source

Luminaire

AuroRing-254mm-RGBW BLUE-LumiMax-35D

Basic Luminous Shape

NONE

Item No.

Manufacturer

Luminoscape

Main Light Measurement Results

Output – Total Lumen

500 lm

Efficiency

7 lm/W

Peak Intensity

901 cd


Correlated Color Temperature, CCT

2700 K

Color Rendering Index

CRI 85.0


Polar light distribution diagram



Test report


Light measurement results

Beam details



Luminaire budgetary diagram


LAMPS (number of lamps)




Test report

Light measurement results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)



Test report


Light measurement results

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	170	lm	34%
Medium (30-60°)	61.8	lm	12.4%
High (60-80°)	8	lm	1.6%
Very High	0	lm	0%

Back Light

Low (0-30°)	183.1	lm	36.6%
Medium (30-60°)	68.2	lm	13.6%
High (60-80°)	8.9	lm	1.8%
Very High	0	lm	0%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	500	lm	100%
-----	-----	----	------