

Test report

Light measurement results

Laboratory and Equipment

Test lab
Spectrometer Manufacturer and Model
Measurement date

7/17/2025

Measurement Conditions

Tested c-planes
Tested gamma angles
Input Power

25 – distance {C_PLANES_DIST}°
181 – {H_PLANES_DIST}°
71.8 W

Tested Light Source
Luminaire
Basic Luminous Shape
Item No.
Manufacturer


AuroRing-254mm-RGBW GREEN-LumiMax-35D
NONE
Luminoscape

Main Light Measurement Results

Output – Total Lumen
Efficiency
Peak Intensity
Correlated Color Temperature, CCT
Color Rendering Index

2720 lm
38 lm/W
4879 cd
2700 K
CRI 85.0


Polar light distribution diagram



Test report


Light measurement results

Beam details



Luminaire budgetary diagram


LAMPS (number of lamps)




Test report

Light measurement results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)



Test report


Light measurement results

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U0 G0



Forward Light

Low (0-30°)	921.2	lm	33.9%
Medium (30-60°)	334.7	lm	12.3%
High (60-80°)	49.8	lm	1.8%
Very High	1.2	lm	0%

Back Light

Low (0-30°)	989	lm	36.4%
Medium (30-60°)	367.6	lm	13.5%
High (60-80°)	54.8	lm	2%
Very High	1.8	lm	0.1%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	2720	lm	100%
-----	------	----	------