

Test report

Light measurement results

Laboratory and Equipment

Test lab
Spectrometer Manufacturer and Model
Measurement date

7/18/2025

Measurement Conditions

Tested c-planes
Tested gamma angles
Input Power

25 – distance {C_PLANES_DIST}°
181 – {H_PLANES_DIST}°
71.5 W

Tested Light Source
Luminaire
Basic Luminous Shape
Item No.
Manufacturer


AuroRing-254mm-RGBW GREEN-LumiMax-45D
NONE
Luminoscape

Main Light Measurement Results

Output – Total Lumen
Efficiency
Peak Intensity
Correlated Color Temperature, CCT
Color Rendering Index

2717 lm
38 lm/W
3809 cd
2700 K
CRI 85.0


Polar light distribution diagram



Test report


Light measurement results

Beam details



Luminaire budgetary diagram


LAMPS (number of lamps)




Test report

Light measurement results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)



Test report


Light measurement results

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U0 G0



Forward Light

Low (0-30°)	931.2	lm	34.3%
Medium (30-60°)	348.5	lm	12.8%
High (60-80°)	63.9	lm	2.4%
Very High	2.1	lm	0.1%

Back Light

Low (0-30°)	947.6	lm	34.9%
Medium (30-60°)	356	lm	13.1%
High (60-80°)	65.6	lm	2.4%
Very High	2.2	lm	0.1%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	2717	lm	100%
-----	------	----	------