

Test report

Light measurement results

Laboratory and Equipment

Test lab
Spectrometer Manufacturer and Model
Measurement date

7/14/2025

Measurement Conditions

Tested c-planes
Tested gamma angles
Input Power

25 – distance {C_PLANES_DIST}°
181 – {H_PLANES_DIST}°
36.1 W

Tested Light Source
Luminaire
Basic Luminous Shape
Item No.
Manufacturer


AuroRing Mini-212mm-RGBW BLUE-LumiMax-35D
NONE
Luminoscape

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity
Correlated Color Temperature, CCT
Color Rendering Index

361 lm – 0% / 100%
10 lm/W
616 cd
2700 K
CRI 85.0


Polar light distribution diagram



Test report


Light measurement results

Beam details



Luminaire budgetary diagram


LAMPS (number of lamps)




Test report

Light measurement results

Iso-intensity Diagram (Iso-candela)




Iso-illuminance Diagram (Iso-lux)



Test report


Light measurement results

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	118.2	lm	32.8%
Medium (30-60°)	46.7	lm	12.9%
High (60-80°)	7.2	lm	2%
Very High	0.1	lm	0%

Back Light

Low (0-30°)	130.3	lm	36.1%
Medium (30-60°)	50.8	lm	14.1%
High (60-80°)	7.4	lm	2.1%
Very High	0.1	lm	0%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	361	lm	100%
-----	-----	----	------