

Test report

Light measurement results

Print date 10/7/2025

Laboratory and Equipment

Test lab

Spectrometer Manufacturer and Model

Measurement date

9/22/2023

Measurement Conditions

Tested c-planes

Tested gamma angles

Input Power

25.0 W

Tested Light Source

Luminaire

Aurora-RGBW 6500K-10D-Rev1

Basic Luminous Shape

NONE

Item No.

Manufacturer

Luminoscape

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)

1430 lm

Efficiency

57 lm/W

Peak Intensity

33198 cd


Correlated Color Temperature, CCT

6500 K

Color Rendering Index

CRI 80.0

Polar light distribution diagram




Test report

Light measurement results


Print date 10/7/2025

Beam details



Luminaire budgetary diagram

LAMPS (number of lamps)




Test report


Light measurement results

Print date 10/7/2025

Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Test report

Light measurement results


Print date 10/7/2025

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U2 G0



Forward Light

Low (0-30°)	681.9	lm	47.7%
Medium (30-60°)	29.2	lm	2%
High (60-80°)	5	lm	0.3%
Very High	1.2	lm	0.1%

Back Light

Low (0-30°)	611.4	lm	42.8%
Medium (30-60°)	55.4	lm	3.9%
High (60-80°)	11.3	lm	0.8%
Very High	3.2	lm	0.2%

Uplight

Low (90-100°)	3.7	lm	0.3%
High (100-180°)	27.6	lm	1.9%

Total

Sum	1430	lm	100%
-----	------	----	------