

Test report

Light measurement results

Print date 10/7/2025

Laboratory and Equipment

Test lab
Spectrometer Manufacturer and Model
Measurement date 9/22/2023


Measurement Conditions

Tested c-planes
Tested gamma angles
Input Power 100 W

Tested Light Source
Luminaire Aurora-RGBW ALL-10D-Rev1
Basic Luminous Shape NONE
Item No.
Manufacturer Luminoscape

Main Light Measurement Results
Output – Total Lumen (Up% / Down%) 3830 lm
Efficiency 38 lm/W
Peak Intensity 87903 cd
Correlated Color Temperature, CCT
Color Rendering Index

Polar light distribution diagram




Test report

Light measurement results


Print date 10/7/2025

Beam details



Luminaire budgetary diagram

LAMPS (number of lamps)




Test report


Light measurement results

Print date 10/7/2025

Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Test report

Light measurement results


Print date 10/7/2025

Linear intensity distribution



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B3 U3 G0



Forward Light

Low (0-30°)	1838.1 lm	48%
Medium (30-60°)	80.3 lm	2.1%
High (60-80°)	13.7 lm	0.4%
Very High	3.4 lm	0.1%

Back Light

Low (0-30°)	1621.4 lm	42.3%
Medium (30-60°)	149.9 lm	3.9%
High (60-80°)	30.5 lm	0.8%
Very High	8.9 lm	0.2%

Uplight

Low (90-100°)	10 lm	0.3%
High (100-180°)	73.9 lm	1.9%

Total

Sum	3830 lm	100%
-----	---------	------